

Eigenschaften

| | |
|--------------------|--------------------------|
| Anschluss 1 | metrisches Muttergewinde |
| Bauart | Überwurfmutter |
| Norm | DIN 3870 |
| Werkstoff | Messing |



Artikel

| Bezeichnung | Baureihe | Ø d2 (mm) | G1 | L1 (mm) | S1 |
|----------------|----------|--------------|------------|------------|----|
| UEM 04 LL MG | LL | 4 | M 8 x 1 | 11,0 | 10 |
| UEM 05 LL MG | LL | 5 | M 10 x 1 | 11,5 | 12 |
| UEM 06 LL MG | LL | 6 | M 10 x 1 | 11,5 | 12 |
| UEM 08 LL MG | LL | 8 | M 12 x 1 | 12,0 | 14 |
| UEM 10 LL MG | LL | 10 | M 14 x 1 | 12,5 | 17 |
| UEM 12 LL MG | LL | 12 | M 16 x 1 | 13,0 | 19 |
| | | | | | |
| UEM NW 04 L MG | L | 6 | M 12 x 1,5 | 14,5 | 14 |
| UEM NW 06 L MG | L | 8 | M 14 x 1,5 | 14,5 | 17 |
| UEM NW 08 L MG | L | 10 | M 16 x 1,5 | 15,5 | 19 |
| UEM NW 10 L MG | L | 12 | M 18 x 1,5 | 15,5 | 22 |
| UEM NW 13 L MG | L | 15 | M 22 x 1,5 | 17,0 | 27 |
| UEM NW 16 L MG | L | 18 | M 26 x 1,5 | 18,0 | 32 |
| UEM NW 20 L MG | L | 22 | M 30 x 2 | 20,0 | 36 |
| UEM NW 25 L MG | L | 28 | M 36 x 2 | 21,0 | 41 |
| UEM NW 32 L MG | L | 35 | M 45 x 2 | 24,0 | 50 |
| UEM NW 40 L MG | L | 42 | M 52 x 2 | 24,0 | 60 |
| | | | | | |
| UEM NW 03 S MG | S | 6 | M 14 x 1,5 | 16,5 | 17 |
| UEM NW 04 S MG | S | 8 | M 16 x 1,5 | 16,5 | 19 |
| UEM NW 06 S MG | S | 10 | M 18 x 1,5 | 17,5 | 22 |
| UEM NW 08 S MG | S | 12 | M 20 x 1,5 | 17,5 | 24 |
| UEM NW 10 S MG | S | 14 | M 22 x 1,5 | 20,5 | 27 |
| UEM NW 13 S MG | S | 16 | M 24 x 1,5 | 20,5 | 30 |
| UEM NW 16 S MG | S | 20 | M 30 x 2 | 24,0 | 36 |
| UEM NW 20 S MG | S | 25 | M 36 x 2 | 27,0 | 46 |
| UEM NW 25 S MG | S | 30 | M 42 x 2 | 29,0 | 50 |
| UEM NW 32 S MG | S | 38 | M 52 x 2 | 32,5 | 60 |

Baureihe: LL = Sehr Leicht L = Leicht S = Schwer – PN = Nenndruck PB = max. Betriebsdruck – Ø d2 = Rohraußendurchmesser

Produktvarianten

| | |
|--------|-------------------------------|
| UEM | Überwurfmutter, Stahl |
| UEM VA | Überwurfmutter, VA, Edelstahl |