


Bauart Druckring für Bördelanschluss

Werkstoff Edelstahl





Artikel				
Bezeichnung	Baureihe	Betriebsdruck	Ø d2 (mm)	L1 (mm)
DRD 06 VA	L/S	PN 630	6	10,5
DRD 08 VA	L/S	PN 630	8	11,0
DRD 10 VA	L/S	PN 630	10	12,5
DRD 12 VA	L/S	PN 630	12	13,0
DRD 15 VA	L	PN 400	15	14,0
DRD 18 VA	L	PN 315	18	14,5
DRD 22 VA	L	PN 315	22	18,0
DRD 28 VA	L	PN 250	28	17,0
DRD 35 VA	L	PN 250	35	19,0
DRD 42 VA	L	PN 250	42	21,0
DRD 14 VA	S	PN 630	14	14,5
DRD 16 VA	S	PN 400	16	17,0
DRD 20 VA	S	PN 400	20	17,5
DRD 25 VA	S	PN 400	25	20,0
DRD 30 VA	S	PN 400	30	21,5
DRD 38 VA	S	PN 315	38	26,5

 $PN = Nenndruck \quad PB = max. \ Betriebsdruck \ - \ Baureihe: \ LL = Sehr \ Leicht \quad L = Leicht \quad S = Schwer \ Leicht \quad S = Schwer \$

Produktvarianten

DRD Druckring für Bördelanschluss, Stahl