
Lötstutzen AGR



Eigenschaften				
Anschluss 1	Lötanschluss			
Anschluss 2	BSP-Außengewinde zylindrisch			
Dichtform 2	60° Innenkonus			
Bauart	Löt-Stutzen			
Bauform	gerade			
Werkstoff	Stahl			
Oberfläche	geölt			





Artikel					
Bezeichnung	Ø d (mm)	G1	L1 (mm)	SW (mm)	
LOET 04 HB 08	8	G 1/4" -19	21,0	19	
LOET 04 HB 12	12	G 1/4" -19	21,0	19	
LOET 06 HB 14	14	G 3/8" -19	27,0	24	
LOET 06 HB 16	16	G 3/8" -19	27,0	24	
LOET 08 HB 14	14	G 1/2" -14	29,5	29	
LOET 08 HB 16	16	G 1/2" -14	29,5	24	
LOET 08 HB 18	18	G 1/2" -14	29,5	29	
LOET 08 HB 20	20	G 1/2" -14	32,5	29	
LOET 12 HB 20	20	G 3/4" -14	37,5	35	
LOET 12 HB 25	25	G 3/4" -14	37,5	35	
LOET 16 HB 25	25	G 1" -11	41,0	43	
LOET 16 HB 30	30	G 1" -11	41,0	43	

Ø d = Rohr-Außendurchmesser