


Eigenschaften					
Anschluss 1	metrisches Außengewinde zylindrisch				
Dichtform 1	Form A				
Bauart	Verschluss-Schraube mit Innensechskant				
Bauform	gerade				
Norm	DIN 908				
Werkstoff	Stahl				
Oberfläche	galvanisch beschichtet				





Artikel						
Bezeichnung	G1	D	i	L1	SW	
		(mm)	(mm)	(mm)	(mm)	
FHM 90-10	M 10 x 1	14	8	11	5	
FHM 90-12	M 12 x 1,5	17	12	15	6	
FHM 90-14	M 14 x 1,5	19	12	15	6	
FHM 90-16	M 16 x 1,5	21	12	15	8	
FHM 90-18	M 18 x 1,5	23	12	16	8	
FHM 90-20	M 20 x 1,5	25	14	18	10	
FHM 90-22	M 22 x 1,5	27	14	18	10	
FHM 90-24	M 24 x 1,5	29	14	18	12	
FHM 90-26	M 26 x 1,5	31	16	20	12	
FHM 90-30-1.5	M 30 x 1,5	36	16	20	17	
FHM 90-36-1.5	M 36 x 1,5	42	16	21	19	
FHM 90-42-1.5	M 42 x 1,5	49	16	21	22	
FHM 90-48-1.5	M 48 x 1,5	55	16	21	24	
FHM 90-52-1.5	M 52 x 1,5	60	16	21	24	

PN = Nenndruck PB = max. Betriebsdruck