

G HB IR VA

Aufschraub-Stutzen

Eigenschaften

| | |
|--------------------|------------------------------|
| Anschluss 1 | BSP-Außengewinde zylindrisch |
| Dichtform 1 | 60° Innenkonus |
| Anschluss 2 | BSP-Innengewinde zylindrisch |
| Dichtform 2 | flachdichtend |
| Bauart | Aufschraub-Stutzen |
| Bauform | gerade |
| Werkstoff | Edelstahl |



Artikel

| Bezeichnung | G1 | G2 | SW (mm) |
|----------------------|--------------|--------------|------------|
| G HB 02 IR VA | G 1/8" -28 | G 1/8" -28 | 17 |
| G HB 04 IR VA | G 1/4" -19 | G 1/4" -19 | 19 |
| G HB 06 IR VA | G 3/8" -19 | G 3/8" -19 | 24 |
| G HB 08 IR VA | G 1/2" -14 | G 1/2" -14 | 27 |
| G HB 12 IR VA | G 3/4" -14 | G 3/4" -14 | 32 |
| G HB 16 IR VA | G 1" -11 | G 1" -11 | 41 |
| G HB 20 IR VA | G 1.1/4" -11 | G 1.1/4" -11 | 50 |
| G HB 24 IR VA | G 1.1/2" -11 | G 1.1/2" -11 | 55 |
| G HB 32 IR VA | G 2" -11 | G 2" -11 | 70 |

SW = Schlüsselweite

Produktvarianten

| | |
|----------------|---------------------------|
| G HB IR | Aufschraub-Stutzen, Stahl |
|----------------|---------------------------|