


### Eigenschaften

<b>Anschluss 1</b>	NPT-Innengewinde
<b>Dichtform 1</b>	gewindedichtend
<b>Anschluss 2</b>	NPT-Innengewinde
<b>Dichtform 2</b>	gewindedichtend
<b>Bauart</b>	Verbindungs-Stutzen
<b>Bauform</b>	gerade
<b>Werkstoff</b>	Edelstahl



### Artikel

Bezeichnung	G1	G2	SW (mm)
<b>G IN 02 VA</b>	1/8" -27 NPT	1/8" -27 NPT	16
<b>G IN 04 VA</b>	1/4" -18 NPT	1/4" -18 NPT	19
<b>G 06 IN 04 VA</b>	3/8" -18 NPT	1/4" -18 NPT	22
<b>G IN 06 VA</b>	3/8" -18 NPT	3/8" -18 NPT	22
<b>G 08 IN 06 VA</b>	1/2" -14 NPT	3/8" -18 NPT	29
<b>G IN 08 VA</b>	1/2" -14 NPT	1/2" -14 NPT	30
<b>G 12 IN 04 VA</b>	3/4" -14 NPT	1/4" -18 NPT	35
<b>G IN 12 VA</b>	3/4" -14 NPT	3/4" -14 NPT	36
<b>G IN 16 VA</b>	1" -11,5 NPT	1" -11,5 NPT	41

SW = Schlüsselweite

### Produktvarianten

<b>G IN</b>	Verbindungs-Stutzen, Stahl
-------------	----------------------------