
SFH (6000 PSI) CAT Flanschhälfte 6000 PSI (CAT)



Eigenschaften				
geeignet für	Caterpillar			
Werkstoff	Stahl			
Oberfläche	galvanisch beschichtet			





Hinweis

Empfohlende Schrauben sind in den Spalten M (metr) oder M (unc) aufgeführt.

Artikel									
Flanschgröße	PB 10.9 (bar)	A (mm)	B (mm)	C (mm)	D (mm)	L (mm)	M metr.	M unc	
3/4"	400	42,1	13,3	50,8	71	10,7	M10x35	3/8"x1.1/2"	
1"	400	48,4	13,3	57,2	81	13,0	M12x45	-	
1.1/4"	400	54,8	13,3	66,7	95	15,0	M14x45	-	
1.1/2"	400	64,3	13,3	79,4	11	17,0	M16x55	5/8"x2"	
	3/4" 1" 1.1/4"	(bar) 3/4" 400 1" 400 1.1/4" 400	(bar) (mm) 3/4" 400 42,1 1" 400 48,4 1.1/4" 400 54,8	(bar) (mm) (mm) 3/4" 400 42,1 13,3 1" 400 48,4 13,3 1.1/4" 400 54,8 13,3	(bar) (mm) (mm) (mm) 3/4" 400 42,1 13,3 50,8 1" 400 48,4 13,3 57,2 1.1/4" 400 54,8 13,3 66,7	(bar) (mm) (mm) (mm) (mm) 3/4" 400 42,1 13,3 50,8 71 1" 400 48,4 13,3 57,2 81 1.1/4" 400 54,8 13,3 66,7 95	(bar) (mm) (mm) <t< td=""><td>(bar) (mm) <t< td=""></t<></td></t<>	(bar) (mm) (mm) <t< td=""></t<>	

Zubehör				
AFS SCHR M	Schraubensatz metrisch, Innensechskant			
AFS SCHR U	Schraubensatz UNC, Innensechskant			
SCHRAUBE M	Innensechskantschraube			
SCHRAUBE M VZ	Innensechskantschraube			