



K-XVM ZYL 1

Gerade Einschraubverschraubungen, Außengewinde zylindrisch

HANSA FLEX



Hinweis

Weitere Angaben auf Anfrage.

Artikel

Bezeichnung	Gewinde	für Schlauch	L1 (mm)	SW
K- 07 40 30 03	M 5	5 mm / 3 mm	20,0	8 mm
K- 07 40 30 04	G 1/8	6 mm / 4 mm	27,0	14 mm
K- 07 40 30 05	G 1/8	8 mm / 6 mm	29,0	14 mm
K- 07 40 30 06	G 1/4	6 mm / 4 mm	29,0	17 mm
K- 07 40 30 07	G 1/4	8 mm / 6 mm	31,0	17 mm
K- 07 40 30 08	G 1/4	10 mm / 8 mm	33,0	17 mm
K- 07 40 30 09	G 3/8	8 mm / 6 mm	33,0	19 mm
K- 07 40 30 10	G 3/8	10 mm / 8 mm	35,0	19 mm
K- 07 40 30 11	G 3/8	12 mm / 9 mm	35,0	19 mm
K- 07 40 30 12	G 1/2	10 mm / 8 mm	36,0	24 mm
K- 07 40 30 13	G 1/2	12 mm / 9 mm	36,0	24 mm