

# TR B

Einschlagnippel, RGN

**HANSA FLEX**

## Eigenschaften

|                    |                             |
|--------------------|-----------------------------|
| <b>Anschluss 1</b> | Ringauge metrisch           |
| <b>Dichtform 1</b> | Abdichtung durch Kupferring |
| <b>Kürzel</b>      | RGN                         |
| <b>Norm</b>        | DIN 7642                    |
| <b>Werkstoff</b>   | Stahl                       |
| <b>Oberfläche</b>  | galvanisch beschichtet      |



## Artikel

| Bezeichnung | DN | Size | Zoll  | D1<br>(mm) | L1<br>(mm) |
|-------------|----|------|-------|------------|------------|
| TR 04 B 02  | 5  | 3    | 3/16" | 8          | 24         |
| TR 04 B     | 5  | 3    | 3/16" | 10         | 26         |
| TR 06 B 04  | 6  | 4    | 1/4"  | 10         | 26         |
| TR 06 B     | 6  | 4    | 1/4"  | 12         | 28         |
| TR 06 B 08  | 6  | 4    | 1/4"  | 14         | 28         |
| TR 06 B 10  | 6  | 4    | 1/4"  | 16         | 30         |
| TR 08 B 06  | 8  | 5    | 5/16" | 12         | 34         |
| TR 08 B     | 8  | 5    | 5/16" | 14         | 34         |
| TR 08 B 10  | 8  | 5    | 5/16" | 16         | 36         |
| TR 10 B 08  | 10 | 6    | 3/8"  | 14         | 34         |
| TR 10 B     | 10 | 6    | 3/8"  | 16         | 36         |