


| Eigenschaften |                                     |  |  |  |  |
|---------------|-------------------------------------|--|--|--|--|
| Anschluss 1   | metrisches Außengewinde zylindrisch |  |  |  |  |
| Dichtform 1   | 24° Innenkonus                      |  |  |  |  |
| Norm          | ISO 8434-1                          |  |  |  |  |
| Werkstoff     | Stahl                               |  |  |  |  |
| Oberfläche    | galvanisch beschichtet              |  |  |  |  |





| Artikel     |    |      |       |                  |            |            |
|-------------|----|------|-------|------------------|------------|------------|
| Bezeichnung | DN | Size | Zoll  | für Rohr-Außen-Ø | G1         | L1<br>(mm) |
| TR 04 HL    | 5  | 3    | 3/16" | 6                | M 12 x 1,5 | 30         |
| TR 06 HL    | 6  | 4    | 1/4"  | 8                | M 14 x 1,5 | 31         |
| TR 08 HL 06 | 8  | 5    | 5/16" | 8                | M 14 x 1,5 | 38         |
| TR 08 HL    | 8  | 5    | 5/16" | 10               | M 16 x 1,5 | 38         |
| TR 10 HL 08 | 10 | 6    | 3/8"  | 10               | M 16 x 1,5 | 38         |
| TR 10 HL    | 10 | 6    | 3/8"  | 12               | M 18 x 1,5 | 39         |
| TR 13 HL    | 12 | 8    | 1/2"  | 15               | M 22 x 1,5 | 52         |