

OEL HLPD 46

Revision date: 07.06.2017

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

OEL HLPD 46

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic oil.

Product Categories [PC]: PC 17 Hydraulic fluids.

1.3. Details of the supplier of the safety data sheet

Company name:	HANSA-FLEX AG	
Street:	Zum Panrepel 44	
Place:	D-28307 Bremen	
Telephone:	+49 (0) 421 48907 0	Telefax: +49 (0) 421 48907 48
e-mail:	info@hansa-flex.com	
Internet:	www.hansa-flex.de	

1.4. Emergency telephone

+49 (0) 551-19240

number:

Gif tinformati onszen trum NORD GIZ-NORD

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH208	Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl, 2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Do not handle until all safety precautions have been read and understood.

Discharge into the environment must be avoided.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Contains: Mineral oil, Additive.

OEL HLPD 46

Revision date: 07.06.2017

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic			40 - 50 %
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304			
	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl			0,1 - 1,0 %
	931-384-6		01-2119493620-38	
	Flam. Liq. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H226 H302 H318 H317 H411			
27136-73-8	2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol			0,1- 1,0 %
	248-248-0			
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!
 Move victim out of danger zone.
 Remove contaminated, saturated clothing immediately.
 In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Avoid oil mist
 Move victim to fresh air. Put victim at rest and keep warm.
 Get medical advice/attention if you feel unwell.

After contact with skin

After contact with skin, wash immediately with: Water and soap.
 Immediately remove any contaminated clothing, shoes or stockings.
 In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
 Do NOT induce vomiting. Call a physician immediately.
 No administration in cases of unconsciousness or cramps.

4.2. Most important symptoms and effects, both acute and delayed

No information available.
 In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

OEL HLPD 46

Revision date: 07.06.2017

Page 3 of 9

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, Extinguishing powder, Sand, Water mist, Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Sulphur dioxide (SO₂), Phosphorus oxides, Carbon monoxide.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Respiratory protection necessary at: aerosol or mist generation. (See section 8.)

Avoid contact with skin and eyes. Wear personal protection equipment.

In case of leakage, eliminate all ignition sources. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).

Take up mechanically, placing in appropriate containers for disposal.

Remove from the water surface (e.g. skimming, sucking).

High slip hazard because of leaking or spilled product.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: refer to chapter 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe vapour/aerosol. Provide adequate ventilation.

Avoid contact with skin and eyes. Remove contaminated, saturated clothing immediately.

For industrial purposes only.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Avoid oil mist

When hot, product develops flammable vapours.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Fire class B (DIN EN 2).

OEL HLPD 46

Revision date: 07.06.2017

Page 4 of 9

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

- Only use containers specifically approved for the substance/product.
- Keep container tightly closed and in a well-ventilated place.
- Always close containers tightly after the removal of product.
- Recommended storage temperature: 5 - 30 °C Do not store at temperatures over: 40 °C

Advice on storage compatibility

- Do not store together with: Oxidising agent,
- Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

- Protect against: Heat, Light, moisture. Protect against direct sunlight.

7.3. Specific end use(s)

- Hydraulic oil.
- Observe technical data sheet.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Additional advice on limit values

- Air limit values: Mineral oil mist
- Limit value type (country of origin): US-OSHA PEL-Value: 5 mg/m³
- Limit value type (country of origin): ACGIH STEL-Value: 10 mg/m³

8.2. Exposure controls
Protective and hygiene measures

- Do not eat, drink, smoke or sneeze at the workplace. Avoid contact with skin, eyes and clothes. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. Do not put any product-impregnated cleaning rags into your trouser pockets.

Eye/face protection

- Suitable eye protection: Tightly sealed safety glasses. (DIN EN 166)
- In case of increasing hazard add: Eye-shade.

Hand protection

- Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 420, DIN EN 374.
- Suitable material: NBR (Nitrile rubber), PVC (Polyvinyl chloride), FKM (fluororubber).
- Required properties: liquid-tight.
- penetration time (maximum wearing period): > 240 min.
- Thickness of glove material: 0,4 mm
- Before using check leak tightness / impermeability.

Skin protection

- Handling larger quantities: Wear suitable protective clothing.

Respiratory protection

- With correct and proper use, and under normal conditions, breathing protection is not required.
- Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.
- Suitable respiratory protective equipment: A2/P2 Combination filter device (DIN EN 141)..

Safety Data Sheet

HANSA FLEX

according to Regulation (EC) No 1907/2006

OEL HLPD 46

Revision date: 07.06.2017

Page 5 of 9

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
 Colour: light yellow
 Odour: like: mineral oil.

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: No data available.
 Initial boiling point and boiling range: No data available.
 Pour point: < -21 °C DIN ISO 3016
 Flash point: > 180 °C DIN ISO 2592

Explosive properties

No data available.

Oxidizing properties

No data available.

Vapour pressure: < 0,1 hPa
 (at 20 °C)

Density (at 15 °C): approx. 0,86 - 0,88 g/cm³ DIN 51757

Water solubility: practically insoluble

Viscosity / kinematic: approx. 46 mm²/s DIN 51562
 (at 40 °C)

9.2. Other information

none

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.
 Decomposition takes place from temperatures above: 120 °C

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.
 Do not mix with: Oxidizing agents, strong.

10.4. Conditions to avoid

storage stability: Do not store at temperatures over: 40 °C
 This material is combustible, but will not ignite readily.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.
 In case of fire may be liberated: Carbon dioxide (CO₂), Sulphur dioxide (SO₂), Phosphorus oxides, Carbon monoxide.

OEL HLPD 46

Revision date: 07.06.2017

Page 6 of 9

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic			
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier
	dermal	LD50 > 5000 mg/kg	Rabbit	ECHA Dossier
	inhalative (4 h) aerosol	LC50 > 5,53 mg/l	Rat	ECHA Dossier
	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterfied with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl			
	oral	ATE 500 mg/kg		
27136-73-8	2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol			
	oral	ATE 500 mg/kg		

Irritation and corrosivity

Irritant effect on the skin: On short hand contact: Not an irritant.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Irritant effect on the eye: slightly irritant but not relevant for classification.

Sensitising effects

Respiratory or skin sensitisation: not sensitising. No known symptoms to date.

Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterfied with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl; 2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol: May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The mineral oils in the product contain < 3 % DMSO-extract (IP 346).

STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OEL HLPD 46

Revision date: 07.06.2017

Page 7 of 9

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic				
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier
	Crustacea toxicity	NOEC 10 mg/l	21 d	Daphnia magna (Big water flea)	ECHA Dossier

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	2 - 4 %	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			
	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	7,4 %	28	

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

State of matter: liquid at room temperature.

If product enters soil, it will be mobile and may contaminate groundwater

12.5. Results of PBT and vPvB assessment

PBT: not applicable.

vPvB: not applicable.

12.6. Other adverse effects

No information available.

Further information

Discharge into the environment must be avoided.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)". Dispose of waste according to applicable legislation.

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

Consult the local waste disposal expert about waste disposal.

Observe mixture permissions according to "Altölverordnung (Waste oil directive)".

Waste disposal number of waste from residues/unused products

OEL HLPD 46

Revision date: 07.06.2017

Page 8 of 9

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

Waste disposal number of used product

130110 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; mineral based non-chlorinated hydraulic oils; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: not relevant

14.2. UN proper shipping name: not relevant

14.3. Transport hazard class(es): not relevant

14.4. Packing group: not relevant

Other applicable information (land transport)

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

No information available.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handling (Transport information): No special precautionary measures are necessary. See protective measures under point 7 and 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), solvent-dewaxed light paraffinic

Additional information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

OEL HLPD 46

Revision date: 07.06.2017

Page 9 of 9

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH).

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

Additional information

Restricted to professional users.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 15.

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl, 2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)