


Properties						
Connection 1	BSP external thread, cylindrical					
Sealing form 1	Shape B					
Connection 2 + 3	metric cylindrical outer thread					
Sealing form 2 + 3	24° inner cone					
Design	Screw-in fitting					
Construction	L shaped					
Standard	DIN 2353 ISO 8434-1					
Scope of supply	Socket with union nut and cutting ring					
Material	Steel					
Surface	electro galvanised					





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe

Item											
Identification	Series	Operating pressure	Ø d2 (mm)	G1	Ø D (mm)	i (mm)	L3 (mm)	L4 (mm)	L5 (mm)	AF (mm)	S1
LR NW 20 HL	L	PN 160	22	G 3/4" -14	32	16	44	27,5	26	27	36
LR NW 25 HL	L	PN 160	28	G 1" -11	39	18	47	30,5	30	36	41
LR NW 32 HL	L	PN 160	35	G 1.1/4" -11	49	20	56	34,5	34	41	60
LR NW 40 HL	L	PN 160	42	G 1.1/2" -11	55	22	63	40,0	39	50	60
LR NW 16 HS	S	PN 400	20	G 3/4" -14	32	16	48	26,5	26	27	36
LR NW 20 HS	S	PN 400	25	G 1" -11	39	18	54	30,0	30	36	46
LR NW 25 HS	S	PN 250	30	G 1.1/4" -11	49	20	62	35,5	34	41	50
LR NW 32 HS	S	PN 250	38	G 1.1/2" -11	55	22	63	40,0	39	50	60

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø d2 = External pipe diameter

Product versions				
LR VA	Screw-in fitting, L shaped, Stainless steel			
XLR	Screw-in fitting, L shaped, Steel			