
# LRK VA
Screw-in fitting, L shaped

## Properties

| | |
|---|---|
| **Connection 1** | BSPT conical external threads |
| **Sealing form 1** | thread seal |
| **Connection 2 + 3** | metric cylindrical outer thread |
| **Sealing form 2 + 3** | 24° inner cone |
| **Design** | Screw-in fitting |
| **Construction** | L shaped |
| **Standard** | DIN 2353<br>ISO 8434-1 |
| **Scope of supply** | Socket with union nut and cutting ring |
| **Material** | Stainless steel |






## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

| Identification | Series | Operating pressure | Ø d2 (mm) | G1 | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | AF (mm) | S1 |
|---|---|---|---|---|---|---|---|---|---|---|
| **LR 04 LL VA** | LL | PN 100 | 4 | R 1/8" K | 8 | 21 | 11,0 | 17 | 9 | 10 |
| **LR 06 LL VA** | LL | PN 100 | 6 | R 1/8" K | 8 | 21 | 9,5 | 17 | 9 | 12 |
| **LR 08 LL VA** | LL | PN 100 | 8 | R 1/8" K | 7 | 23 | 11,5 | 20 | 12 | 14 |
| **LR NW 04 HL VA** | L | PN 315 | 6 | R 1/8" K | 8 | 21 | 11,0 | 17 | 12 | 14 |
| **LR NW 04 HL 1/4 VA** | L | PN 315 | 6 | R 1/4" K | 12 | 32 | 17,5 | 27 | 17 | 22 |
| **LR NW 06 HL VA** | L | PN 315 | 8 | R 1/4" K | 12 | 29 | 14,0 | 26 | 12 | 17 |
| **LR NW 08 HL VA** | L | PN 315 | 10 | R 1/4" K | 12 | 30 | 15,0 | 27 | 14 | 19 |
| **LR NW 08 HL 3/8 VA** | L | PN 315 | 10 | R 3/8" K | 12 | 30 | 15,0 | 28 | 17 | 19 |
| **LR NW 10 HL 1/4 VA** | L | PN 315 | 12 | R 1/4" K | 12 | 32 | 17,5 | 27 | 17 | 22 |
| **LR NW 10 HL VA** | L | PN 315 | 12 | R 3/8" K | 12 | 32 | 17,0 | 28 | 17 | 22 |
| **LR NW 10 HL 1/2 VA** | L | PN 315 | 12 | R 1/2" K | 14 | 32 | 17,0 | 34 | 17 | 22 |
| **LR NW 13 HL VA** | L | PN 315 | 15 | R 1/2" K | 14 | 36 | 21,0 | 34 | 19 | 27 |
| **LR NW 16 HL VA** | L | PN 315 | 18 | R 1/2" K | 14 | 40 | 23,5 | 36 | 24 | 32 |
| **LR NW 03 HS VA** | S | PN 400 | 6 | R 1/4" K | 12 | 31 | 16,0 | 26 | 12 | 17 |
| **LR NW 04 HS VA** | S | PN 400 | 8 | R 1/4" K | 13 | 32 | 17,0 | 27 | 14 | 19 |
| **LR NW 06 HS VA** | S | PN 400 | 10 | R 3/8" K | 12 | 34 | 17,5 | 28 | 17 | 22 |
| **LR NW 08 HS VA** | S | PN 400 | 12 | R 3/8" K | 12 | 38 | 21,5 | 28 | 17 | 24 |
| **LR NW 08 HS 1/2 VA** | S | PN 400 | 12 | R 1/2" K | 14 | 38 | 21,5 | 33 | 19 | 24 |
| **LR NW 10 HS VA** | S | PN 400 | 14 | R 1/2" K | 14 | 40 | 22,0 | 32 | 19 | 27 |
| **LR NW 13 HS VA** | S | PN 400 | 16 | R 1/2" K | 14 | 43 | 24,5 | 32 | 24 | 30 |

Series: LL = Very light  L = Light  S = Heavy – PN = Nominal pressure  PB = Max. operating pressure – Ø d2 = External pipe diameter

## Product versions

| | |
|---|---|
| **LRK** | Screw-in fitting, L shaped, Steel |
| **XLRK VA** | Screw-in fitting, L shaped, Stainless steel |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*