


Properties

Connection 1	metric nut thread
Sealing form 1	Pipe socket, pre-assembled
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Design	Adjustable direction fitting
Construction	L shaped
Standard	DIN 2353 ISO 8434-1
Scope of supply	Socket with union nut and cutting ring
Material	Brass



Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G1	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1
VEL NW 04 HL MG	L	PN 200	6	M 12 x 1.5	27	12,0	26,0	12	14
VEL NW 06 HL MG	L	PN 200	8	M 14 x 1.5	29	14,0	27,0	12	17
VEL NW 08 HL MG	L	PN 200	10	M 16 x 1.5	30	15,0	28,5	14	19
VEL NW 10 HL MG	L	PN 200	12	M 18 x 1.5	32	17,0	29,0	17	22
VEL NW 13 HL MG	L	PN 200	15	M 22 x 1.5	36	21,0	32,0	19	27
VEL NW 16 HL MG	L	PN 200	18	M 26 x 1.5	40	23,5	35,0	24	32

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

VEL	Fitting, L shaped, Steel
VEL VA	Fitting, L shaped, Stainless steel