


Properties				
Connection 1	metric nut thread			
Sealing form 1	Pipe socket, pre-assembled			
Connection 2 + 3	metric cylindrical outer thread			
Sealing form 2 + 3	24° inner cone			
Design	Adjustable direction fitting			
Construction	L shaped			
Standard	DIN 2353 ISO 8434-1			
Scope of supply	Socket with union nut and cutting ring			
Material	Brass			





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item									
Identification	Series	Operating pressure	Ø d2 (mm)	G1	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1
VEL NW 04 HL MG	L	PN 200	6	M 12 x 1.5	27	12,0	26,0	12	14
VEL NW 06 HL MG	L	PN 200	8	M 14 x 1.5	29	14,0	27,0	12	17
VEL NW 08 HL MG	L	PN 200	10	M 16 x 1.5	30	15,0	28,5	14	19
VEL NW 10 HL MG	L	PN 200	12	M 18 x 1.5	32	17,0	29,0	17	22
VEL NW 13 HL MG	L	PN 200	15	M 22 x 1.5	36	21,0	32,0	19	27
VEL NW 16 HL MG	L	PN 200	18	M 26 x 1.5	40	23,5	35,0	24	32

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø d2 = External pipe diameter

Product versions		
VEL	Fitting, L shaped, Steel	
VEL VA	Fitting, L shaped, Stainless steel	