
XELOMK
Screw-in fitting, L shaped

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	O-ring and spacer diaphragm ring
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Design	Adjustable direction screw-in fitting
Construction	L shaped
Standard	ISO 8434-1
Scope of supply	Socket (without union nut and cutting ring)
Material	Steel
Surface	electro galvanised





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G1	G2 + G3	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	AF (mm)	S1	OR
XELOMK NW 04 HL	L	PN 315	6	M 10 x 1	M 12 x 1.5	7	14	20	21	14	13	8.1 x 1.6
XELOMK NW 06 HL	L	PN 315	8	M 12 x 1.5	M 14 x 1.5	10	16	22	23	14	17	9.3 x 2.4
XELOMK NW 08 HL	L	PN 315	10	M 14 x 1.5	M 16 x 1.5	9	17	25	24	19	17	11.3 x 2.4
XELOMK NW 10 HL	L	PN 315	12	M 16 x 1.5	M 18 x 1.5	9	19	26	26	19	19	13.3 x 2.4
XELOMK NW 13 HL	L	PN 315	15	M 18 x 1.5	M 22 x 1.5	11	21	30	28	22	22	15.3 x 2.4
XELOMK NW 16 HL	L	PN 315	18	M 22 x 1.5	M 26 x 1.5	11	24	33	31	27	27	19.3 x 2.4
XELOMK NW 20 HL	L	PN 160	22	M 26 x 1.5	M 30 x 2	16	28	35	35	30	32	23.3 x 2.4
XELOMK NW 20 HL 27	L	PN 160	22	M 27 x 2	M 30 x 2	14	28	35	35	30	36	23.6 x 2.9
XELOMK NW 25 HL	L	PN 160	28	M 33 x 2	M 36 x 2	14	31	38	38	36	38	29.5 x 3.0
XELOMK NW 32 HL	L	PN 160	35	M 42 x 2	M 45 x 2	14	38	48	48	50	50	38.0 x 3.0
XELOMK NW 40 HL	L	PN 160	42	M 48 x 2	M 52 x 2	16	38	49	49	50	55	44.5 x 3.0
XELOMK NW 03 HS	S	PN 315	6	M 12 x 1.5	M 14 x 1.5	10	15	22	22	14	17	9.3 x 2.4
XELOMK NW 04 HS	S	PN 315	8	M 14 x 1.5	M 16 x 1.5	10	17	26	24	19	17	11.3 x 2.4
XELOMK NW 06 HS	S	PN 315	10	M 16 x 1.5	M 18 x 1.5	11	18	27	25	19	19	13.3 x 2.4
XELOMK NW 08 HS	S	PN 315	12	M 18 x 1.5	M 20 x 1.5	12	22	31	29	22	22	15.3 x 2.4
XELOMK NW 10 HS	S	PN 315	14	M 20 x 1.5	M 22 x 1.5	14	25	35	33	27	27	17.3 x 2.4
XELOMK NW 13 HS	S	PN 315	16	M 22 x 1.5	M 24 x 1.5	14	25	35	33	27	27	19.3 x 2.4
XELOMK NW 16 HS	S	PN 315	20	M 27 x 2	M 30 x 2	16	28	39	38	30	32	23.6 x 2.9
XELOMK NW 20 HS	S	PN 315	25	M 33 x 2	M 36 x 2	16	30	44	42	36	38	29.5 x 3.0
XELOMK NW 25 HS	S	PN 250	30	M 42 x 2	M 42 x 2	17	36	51	49	50	50	38.0 x 2.0
XELOMK NW 32 HS	S	PN 200	38	M 48 x 2	M 52 x 2	19	34	54	50	50	55	44.5 x 3.0

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

ELOMK Screw-in fitting, L shaped, Socket with union nut and cutting ring

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.