
# XLMK VA
Screw-in fitting, L shaped

## Properties

| | |
|---|---|
| **Connection 1** | metric conical outer thread |
| **Sealing form 1** | thread seal |
| **Connection 2 + 3** | metric cylindrical outer thread |
| **Sealing form 2 + 3** | 24° inner cone |
| **Design** | Screw-in fitting |
| **Construction** | L shaped |
| **Standard** | DIN 2353 |
| **Scope of supply** | Socket (without union nut and cutting ring) |
| **Material** | Stainless steel |






## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

| Identification | Series | Operating pressure | Ø d2 (mm) | G | i (mm) | L4 (mm) | L5 (mm) | L7 (mm) | AF (mm) |
|---|---|---|---|---|---|---|---|---|---|
| **XLM NW 04 HL VA** | L | PN 315 | 6 | M 10 x 1 K | 8 | 12,0 | 20 | 19 | 12 |
| **XLM NW 06 HL VA** | L | PN 315 | 8 | M 12 x 1.5 K | 12 | 14,0 | 26 | 21 | 12 |
| **XLM NW 08 HL VA** | L | PN 315 | 10 | M 14 x 1.5 K | 12 | 15,0 | 27 | 22 | 14 |
| **XLM NW 10 HL VA** | L | PN 315 | 12 | M 16 x 1.5 K | 12 | 17,0 | 28 | 24 | 17 |
| **XLM NW 13 HL VA** | L | PN 316 | 15 | M 18 x 1.5 K | 12 | 21,0 | 32 | 26 | 19 |
| **XLM NW 16 HL VA** | L | PN 315 | 18 | M 22 x 1.5 K | 14 | 23,5 | 36 | 31 | 24 |
| | | | | | | | | | |
| **XLM NW 03 HS VA** | S | PN 400 | 6 | M 12 x 1.5 K | 12 | 16,0 | 26 | 23 | 12 |
| **XLM NW 04 HS VA** | S | PN 400 | 8 | M 14 x 1.5 K | 12 | 17,0 | 27 | 24 | 14 |
| **XLM NW 06 HS VA** | S | PN 400 | 10 | M 16 x 1.5 K | 12 | 17,5 | 28 | 25 | 17 |
| **XLM NW 08 HS VA** | S | PN 400 | 12 | M 18 x 1.5 K | 12 | 21,5 | 28 | 29 | 17 |
| **XLM NW 10 HS VA** | S | PN 400 | 14 | M 20 x 1.5 K | 14 | 22,0 | 32 | 30 | 19 |
| **XLM NW 13 HS VA** | S | PN 400 | 16 | M 22 x 1.5 K | 14 | 24,5 | 32 | 33 | 24 |

Series: LL = Very light  L = Light  S = Heavy – PN = Nominal pressure  PB = Max. operating pressure – Ø d2 = External pipe diameter

## Product versions

| | |
|---|---|
| **XLMK** | Screw-in fitting, L shaped, Steel |
| **LMK VA** | Screw-in fitting, L shaped, Stainless steel |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*