XVEL Fitting, L shaped



Properties

1 Toporado	
Connection 1	metric nut thread
Sealing form 1	Pipe socket, pre-assembled
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Design	Adjustable direction fitting
Construction	L shaped
Standard	DIN 2353 ISO 8434-1
Scope of supply	Socket (without union nut and cutting ring) pre-assembled
Material	Steel
Surface	electro galvanised





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item Identification Series Operating pressure Ød2 G1 L2 L5 L7 AF **S**1 (mm) (mm (mr (mn XVEL NW 04 HL L PN 315 6 M 12 x 1.5 12,0 26,0 19 12 14 XVEL NW 06 HL PN 315 8 M 14 x 1.5 14,0 27,5 21 17 L 12 XVEL NW 08 HL L PN 315 10 M 16 x 1.5 15,0 29,0 22 14 19 PN 315 29,5 12 17,0 24 17 22 XVEL NW 10 HL L M 18 x 1.5 PN 315 15 28 19 XVEL NW 13 HL M 22 x 1.5 21,0 32,5 27 L PN 315 18 23,5 35,5 31 24 32 XVEL NW 16 HL M 26 x 1.5 L XVEL NW 20 HL PN 160 22 M 30 x 2 27,5 38,5 35 27 36 L XVEL NW 25 HL L PN 160 28 M 36 x 2 30,5 41,5 38 36 41 XVEL NW 32 HL L PN 160 35 M 45 x 2 34,5 51,0 45 41 50 XVEL NW 40 HL L PN 160 42 M 52 x 2 40,0 56,0 51 50 60 23 XVEL NW 03 HS PN 630 6 27.0 S M 14 x 1.5 16,0 12 17 XVEL NW 04 HS S PN 630 8 M 16 x 1.5 17.0 27,5 24 14 19 XVEL NW 06 HS S PN 630 10 M 18 x 1.5 17,5 30,0 25 17 22 XVEL NW 08 HS S PN 630 12 M 20 x 1.5 21,5 31,0 29 17 24 **XVEL NW 10 HS** S PN 630 14 M 22 x 1.5 22,0 35,0 30 19 27 XVEL NW 13 HS S PN 400 16 M 24 x 1.5 24,5 36,5 33 24 30 **XVEL NW 16 HS** S PN 400 20 M 30 x 2 26,5 44,5 37 27 36 S XVEL NW 20 HS PN 400 25 M 36 x 2 30,0 50,0 42 36 46 M 42 x 2 49 **XVEL NW 25 HS** S PN 400 30 35,5 55,0 41 50 **XVEL NW 32 HS** S PN 315 38 M 52 x 2 41.0 63,0 57 50 60

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø d2 = External pipe diameter

Product versions

XVEL VA	Fitting, L shaped, Stainless steel
VEL	Fitting, L shaped, Steel