

XDTM VA

Banjo fitting, throttle free, T shaped

HANSA FLEX

Properties

| | |
|---------------------------|---|
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | Edge sealing ring |
| Connection 2 + 3 | metric cylindrical outer thread |
| Sealing form 2 + 3 | 24° inner cone |
| Design | Banjo coupling, throttle free |
| Construction | T shaped |
| Standard | ISO 8434-1 |
| Scope of supply | Socket (without union nut and cutting ring) |
| Material | Stainless steel |



Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

| Identification | Series | Operating pressure | Ø d2 (mm) | G | Ø D (mm) | i (mm) | L1 (mm) | L2 (mm) | L4 (mm) | L7 (mm) | AF (mm) | S1 | S2 |
|------------------|--------|--------------------|--------------|------------|-------------|-----------|------------|------------|------------|------------|------------|----|----|
| XDTM NW 04 HL VA | L | PN 160 | 6 | M 10 x 1 | 14,0 | 8 | 24 | 12 | 12,0 | 19 | 18 | 6 | 6 |
| XDTM NW 06 HL VA | L | PN 160 | 8 | M 12 x 1.5 | 17,0 | 12 | 27 | 14 | 13,0 | 20 | 20 | 6 | 6 |
| XDTM NW 08 HL VA | L | PN 100 | 10 | M 14 x 1.5 | 19,0 | 12 | 30 | 15 | 15,0 | 22 | 22 | 8 | 8 |
| XDTM NW 10 HL VA | L | PN 100 | 12 | M 16 x 1.5 | 21,0 | 12 | 36 | 18 | 17,5 | 24 | 27 | 10 | 10 |
| XDTM NW 13 HL VA | L | PN 100 | 15 | M 18 x 1.5 | 23,0 | 12 | 39 | 19 | 20,0 | 27 | 30 | 12 | 12 |
| XDTM NW 16 HL VA | L | PN 100 | 18 | M 22 x 1.5 | 27,0 | 14 | 41 | 20 | 20,5 | 28 | 32 | 14 | 14 |
| XDTM NW 20 HL VA | L | PN 100 | 22 | M 26 x 1.5 | 31,0 | 16 | 46 | 22 | 24,5 | 32 | 36 | 17 | 17 |
| XDTM NW 25 HL VA | L | PN 100 | 28 | M 33 x 2 | 39,0 | 18 | 58 | 29 | 29,5 | 37 | 46 | 22 | 22 |
| XDTM NW 32 HL VA | L | PN 63 | 35 | M 42 x 2 | 49,0 | 20 | 69 | 33 | 33,0 | 44 | 55 | 27 | 27 |
| XDTM NW 40 HL VA | L | PN 63 | 42 | M 48 x 2 | 55,0 | 22 | 84 | 41 | 40,0 | 51 | 65 | 32 | 32 |

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

| | |
|---------------|---|
| XDTM | Banjo fitting, throttle free, T shaped, Socket (without union nut and cutting ring) |
| DTM VA | Banjo fitting, throttle free, T shaped, Socket with union nut and cutting ring |