


| Properties         |   |
|--------------------|---|
| Connection 1       | BSP external thread, cylindrical            |
| Sealing form 1     | Edge sealing ring                           |
| Connection 2 + 3   | metric cylindrical outer thread             |
| Sealing form 2 + 3 | 24° inner cone                              |
| Design             | Banjo coupling, throttle free               |
| Construction       | T shaped                                    |
| Standard           | ISO 8434-1                                  |
| Scope of supply    | Socket (without union nut and cutting ring) |
| Material           | Stainless steel                             |





## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

| Item             |        |                    |              |              |             |           |            |            |            |            |            |    |    |
|------------------|--------|--------------------|--------------|--------------|-------------|-----------|------------|------------|------------|------------|------------|----|----|
| Identification   | Series | Operating pressure | Ø d2<br>(mm) | G            | Ø D<br>(mm) | i<br>(mm) | L1<br>(mm) | L2<br>(mm) | L4<br>(mm) | L7<br>(mm) | AF<br>(mm) | S1 | S2 |
| XDTR NW 04 HL VA | L      | PN 160             | 6            | G 1/8" -28   | 14,0        | 8         | 24         | 12         | 12,0       | 19         | 18         | 6  | 6  |
| XDTR NW 06 HL VA | L      | PN 160             | 8            | G 1/4" -19   | 18,0        | 12        | 30         | 15         | 14,0       | 21         | 22         | 8  | 8  |
| XDTR NW 08 HL VA | L      | PN 100             | 10           | G 1/4" -19   | 18,0        | 12        | 30         | 15         | 15,0       | 22         | 22         | 8  | 8  |
| XDTR NW 10 HL VA | L      | PN 100             | 12           | G 3/8" -19   | 22,0        | 12        | 36         | 18         | 17,5       | 24         | 27         | 10 | 10 |
| XDTR NW 13 HL VA | L      | PN 100             | 15           | G 1/2" -14   | 26,0        | 14        | 40         | 20         | 20,0       | 27         | 30         | 12 | 12 |
| XDTR NW 16 HL VA | L      | PN 100             | 18           | G 1/2" -14   | 26,0        | 14        | 40         | 20         | 19,5       | 27         | 30         | 12 | 12 |
| XDTR NW 20 HL VA | L      | PN 100             | 22           | G 3/4" -14   | 32,0        | 16        | 52         | 25         | 27,0       | 34         | 41         | 17 | 17 |
| XDTR NW 25 HL VA | L      | PN 100             | 28           | G 1" -11     | 39,0        | 18        | 58         | 29         | 29,5       | 37         | 46         | 22 | 22 |
| XDTR NW 32 HL VA | L      | PN 63              | 35           | G 1.1/4" -11 | 49,0        | 20        | 69         | 34         | 33,0       | 44         | 55         | 27 | 27 |
| XDTR NW 40 HL VA | L      | PN 63              | 42           | G 1.1/2" -11 | 55,0        | 22        | 84         | 41         | 40,0       | 51         | 65         | 32 | 32 |

 $Series: LL = Very \ light \quad L = Light \quad S = Heavy - PN = Nominal \ pressure \quad PB = Max. \ operating \ pressure - \varnothing \ d2 = External \ pipe \ diameter$ 

| Product versions |   |  |  |  |  |
|------------------|---|--|--|--|--|
| XDTR             | Banjo fitting, throttle free, T shaped, Socket (without union nut and cutting ring) |  |  |  |  |
| DTR VA           | Banjo fitting, throttle free, T shaped. Socket with union nut and cutting ring      |  |  |  |  |