


# SA DKOL

## Welded on sealing cone

### Properties

<b>Connection 1</b>	Welded on socket for metric pipe
<b>Sealing form 2</b>	24° outer cone with O-ring
<b>Design</b>	Welded on sealing cone
<b>Construction</b>	straight
<b>Standard</b>	DIN 3865 ISO 8434-1
<b>Material</b>	Steel
<b>Surface</b>	phosphate treated and oiled (Znphr5f)



### Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

### Item

Identification	Series	Operating pressure	Ø d1 (mm)	Ø d2 (mm)	L1 (mm)	L2 (mm)	OR
SA NW 04 DKOL 1	L	PN 315	4	6	32,0	30,5	4.0 x 1.5
SA NW 06 DKOL 1	L	PN 315	6	8	32,0	30,5	6.0 x 1.5
SA NW 08 DKOL 1	L	PN 249	8	10	33,5	32,5	7.5 x 1.5
SA NW 10 DKOL 1.5	L	PN 315	9	12	33,5	32,5	9.0 x 1.5
SA NW 13 DKOL 2.5	L	PN 315	10	15	35,0	34,5	12.0 x 2.0
SA NW 16 DKOL 2.5	L	PN 315	13	18	37,0	36,0	15.0 x 2.0
SA NW 20 DKOL 2.5	L	PN 160	17	22	39,5	37,5	20.0 x 2.0
SA NW 25 DKOL 2.5	L	PN 160	23	28	42,5	41,0	26.0 x 2.0
SA NW 25 DKOL 3	L	PN 160	22	28	42,5	41,0	26.0 x 2.0
SA NW 32 DKOL 3	L	PN 160	29	35	49,4	47,0	32.0 x 2.5
SA NW 32 DKOL 3.5	L	PN 160	28	35	49,5	47,0	32.0 x 2.5
SA NW 40 DKOL 2	L	PN 129	38	42	50,0	47,0	38.0 x 2.5
SA NW 40 DKOL 3	L	PN 160	36	42	50,0	47,0	38.0 x 2.5

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – d2 = for external pipe diameter

### Product versions

SA DKOL VA Welded on sealing cone, Stainless steel