XT
Fitting, T shaped

HANSA-FLEX

Properties

Connection 1 - 3	metric cylindrical outer thread
Sealing form 1 - 3	24° inner cone
Design	Fitting
Construction	T shaped
Standard	DIN 2353 ISO 8434-1
Scope of supply	Socket (without union nut and cutting ring)
Material	Steel
Surface	electro galvanised





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G1 - G3	L2 (mm)	L7 (mm)	AF (mm)
XT 04 LL	LL	PN 100	4	M 8 x 1	11,0	15	9
XT 05 LL	LL	PN 100	5	M 10 x 1	9,5	15	9
XT 06 LL	LL	PN 100	6	M 10 x 1	9,5	15	9
XT 08 LL	LL	PN 100	8	M 12 x 1	11,5	17	12
XT 10 LL	LL	PN 100	10	M 14 x 1	12,5	18	12
XT 12 LL	LL	PN 100	12	M 16 x 1	15,0	21	14
XT NW 04 HL	L	PN 315	6	M 12 x 1.5	12,0	19	12
XT NW 06 HL	L	PN 315	8	M 14 x 1.5	14,0	21	12
XT NW 08 HL	L	PN 315	10	M 16 x 1.5	15,0	22	14
XT NW 10 HL	L	PN 315	12	M 18 x 1.5	17,0	24	17
XT NW 13 HL	L	PN 315	15	M 22 x 1.5	21,0	28	19
XT NW 16 HL	L	PN 315	18	M 26 x 1.5	23,5	31	24
XT NW 20 HL	L	PN 160	22	M 30 x 2	27,5	35	27
XT NW 25 HL	L	PN 160	28	M 36 x 2	30,5	38	36
XT NW 32 HL	L	PN 160	35	M 45 x 2	34,5	45	41
XT NW 40 HL	L	PN 160	42	M 52 x 2	40,0	51	50
XT NW 03 HS	S	PN 630	6	M 14 x 1.5	16,0	23	12
XT NW 04 HS	S	PN 630	8	M 16 x 1.5	17,0	24	14
XT NW 06 HS	S	PN 630	10	M 18 x 1.5	17,5	25	17
XT NW 08 HS	S	PN 630	12	M 20 x 1.5	21,5	29	17
XT NW 10 HS	S	PN 630	14	M 22 x 1.5	22,0	30	19
XT NW 13 HS	S	PN 400	16	M 24 x 1.5	24,5	33	24
XT NW 16 HS	S	PN 400	20	M 30 x 2	26,5	37	27
XT NW 20 HS	S	PN 400	25	M 36 x 2	30,0	42	36
XT NW 25 HS	S	PN 400	30	M 42 x 2	35,5	49	41
XT NW 32 HS	S	PN 315	38	M 52 x 2	41,0	57	50

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

XT VA	Fitting, T shaped, Stainless steel
T	Fitting, T shaped, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.