
# SV HF

Bulkhead fitting, French series

## Properties

| | |
|---|---|
| **Connection 1 + 2** | metric cylindrical outer thread |
| **Sealing form 1 + 2** | 24° inner cone |
| **Design** | Bulkhead fitting |
| **Construction type** | French series |
| **Construction** | straight |
| **Scope of supply** | Socket with union nut and cutting ring |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

| Identification | Operating pressure | Ø d2 (mm) | G1 | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | AF (mm) | S1 | S2 |
|---|---|---|---|---|---|---|---|---|---|---|
| **SV NW 10 HF** | PN 400 | 13,25 | M 20 x 1.5 | 47,5 | 25 | 32,5 | 10 | 27 | 27 | 27 |
| **SV NW 13 HF** | PN 250 | 16,75 | M 24 x 1.5 | 49,5 | 26 | 34,5 | 11 | 30 | 30 | 30 |
| **SV NW 16 HF** | PN 250 | 21,25 | M 30 x 1.5 | 52,0 | 28 | 37,0 | 13 | 36 | 36 | 36 |
| **SV NW 20 HF** | PN 160 | 26,75 | M 36 x 1.5 | 54,0 | 29 | 40,0 | 15 | 42 | 42 | 42 |
| **SV NW 25 HF** | PN 160 | 33,50 | M 45 x 1.5 | 58,0 | 33 | 44,0 | 19 | 55 | 55 | 55 |

Series: LL = Very light  L = Light  S = Heavy – PN = Nominal pressure  PB = Max. operating pressure – Ø d2 = External pipe diameter

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*