


Properties					
Connection 1	metric nut thread				
Sealing form 1	24° outer cone				
Connection 2	metric cylindrical outer thread				
Sealing form 2	24° inner cone				
Design	Adjustable direction fitting				
Construction type	French series				
Construction	Angle 90°				
Scope of supply	Socket with union nut and cutting ring				
Material	Steel				
Surface	electro galvanised				





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item										
Identification	Operating pressure	Ø d2 (mm)	G1	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1		
VEW NW 10 HF	PN 300	13,25	M 20 x 1.5	25	16	30,5	19	27		
VEW NW 13 HF	PN 300	16,75	M 24 x 1.5	27	18	32,5	24	30		
VEW NW 16 HF	PN 200	21,25	M 30 x 1.5	32	23	36,5	30	36		
VEW NW 20 HF	PN 200	26,75	M 36 x 1.5	36	27	41,0	36	46		
VEW NW 25 HF	PN 160	33,50	M 45 x 1.5	44	35	47,5	46	55		

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø d2 = External pipe diameter