


Properties				
Connection 1	BSPT conical external threads			
Sealing form 1	thread seal			
Connection 2	metric cylindrical outer thread			
Sealing form 2	24° inner cone			
Design	Screw-in fitting			
Construction	straight			
Standard	DIN 2353 ISO 8434-1			
Scope of supply	Socket with union nut and cutting ring			
Material	Brass			





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item									
Identification	Series	Operating pressure	External pipe Ø	G	i (mm)	L1 (mm)	L2 (mm)	S1	S3
VR 04 LL MG	LL	PN 63	4	R 1/8" K	8	26	16,0	11	10
VR 06 LL MG	LL	PN 63	6	R 1/8" K	8	26	14,5	11	12
VR 08 LL 1/4 MG	LL	PN 63	8	R 1/4" K	13	33	21,5	17	14
VR 08 LL MG	LL	PN 63	8	R 1/8" K	8	28	16,5	12	14
VR 10 LL MG	LL	PN 63	10	R 1/4" K	12	32	20,5	14	17
VR 12 LL MG	LL	PN 63	12	R 1/4" K	12	32	20,0	17	19

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø = External pipe diameter

Product versions		
VRK	Screw-in fitting, Steel	
VRK VA	Screw in fitting, Stainless steel	