

# HS R

## Hollow screw

### Properties

|                     |                                  |
|---------------------|----------------------------------|
| <b>Connection 1</b> | BSP external thread, cylindrical |
| <b>Design</b>       | Hollow screw                     |
| <b>Material</b>     | Steel                            |
| <b>Surface</b>      | electro galvanised               |



### Item

| Identification  | G1         | Ø d2<br>(mm) | L2<br>(mm) | m<br>(mm) | S1 |
|-----------------|------------|--------------|------------|-----------|----|
| <b>HS R 1/8</b> | G 1/8" -28 | 9,9          | 19,0       | 5         | 14 |
| <b>HS R 1/4</b> | G 1/4" -19 | 13,1         | 25,5       | 5         | 17 |
| <b>HS R 3/8</b> | G 3/8" -19 | 16,6         | 31,0       | 7         | 22 |
| <b>HS R 1/2</b> | G 1/2" -14 | 20,9         | 40,0       | 8         | 27 |
| <b>HS R 5/8</b> | G 5/8" -14 | 22,9         | 47,0       | 9         | 32 |
| <b>HS R 3/4</b> | G 3/4" -14 | 26,4         | 47,0       | -         | 32 |
| <b>HS R 1</b>   | G 1" -11   | 33,2         | 58,0       | 10        | 41 |

SW, S1, S2 = With across flats

### Product versions

|                |                               |
|----------------|-------------------------------|
| <b>HS R VA</b> | Hollow screw, Stainless steel |
|----------------|-------------------------------|