

# BOOK VA

Flare connection with 2 O-rings

**HANSA FLEX**

## Properties

<b>Design</b>	Flare connection with 2 O-rings
<b>Standard</b>	DIN 3949
<b>Scope of supply</b>	1x union nut, 1x pressure ring, 1x spacer ring
<b>Material</b>	Stainless steel



## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Ordering information

Seals of NBR  
FPM (Viton) on request

## Item

Identification	Series	Operating pressure	for external pipe Ø (mm)	G1
BOOK NW 04 L VA	L	PN 400	6	M 12 x 1.5
BOOK NW 06 L VA	L	PN 400	8	M 14 x 1.5
BOOK NW 08 L VA	L	PN 400	10	M 16 x 1.5
BOOK NW 10 L VA	L	PN 400	12	M 18 x 1.5
BOOK NW 13 L VA	L	PN 400	15	M 22 x 1.5
BOOK NW 16 L VA	L	PN 400	18	M 26 x 1.5
BOOK NW 20 L VA	L	PN 250	22	M 30 x 2
BOOK NW 25 L VA	L	PN 250	28	M 36 x 2
BOOK NW 32 L VA	L	PN 250	35	M 45 x 2
BOOK NW 40 L VA	L	PN 250	42	M 52 x 2
BOOK NW 03 S VA	S	PN 630	6	M 14 x 1.5
BOOK NW 04 S VA	S	PN 630	8	M 16 x 1.5
BOOK NW 06 S VA	S	PN 630	10	M 18 x 1.5
BOOK NW 08 S VA	S	PN 630	12	M 20 x 1.5
BOOK NW 10 S VA	S	PN 630	14	M 22 x 1.5
BOOK NW 13 S VA	S	PN 400	16	M 24 x 1.5
BOOK NW 16 S VA	S	PN 400	20	M 30 x 2
BOOK NW 20 S VA	S	PN 400	25	M 36 x 2
BOOK NW 25 S VA	S	PN 400	30	M 42 x 2
BOOK NW 32 S VA	S	PN 315	38	M 52 x 2

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure

## Product versions

**BOOK** Flare connection with 2 O-rings, 1x union nut, 1x pressure ring, 1x spacer ring