W45 AN HN


Screw-in socket, angle 45°

HANSA-FLEX

Properties

Connection 1	NPT nut thread (NPSM)
Sealing form 1	60° outer cone
Connection 2	NPT external threads
Sealing form 2	thread seal
Design	Screw-in sockets
Construction	Angle 45°
Material	Steel
Surface	electro galvanised





Item

Identification	G1	G2	AF (mm)	S1
W45 AN 02 HN	1/8" -27 NPT	1/8" -27 NPT	11	14
W45 AN 04 HN	1/4" -18 NPT	1/4" -18 NPT	14	18
W45 AN 06 HN	3/8" -18 NPT	3/8" -18 NPT	19	22
W45 AN 06 HN 08	3/8" -18 NPT	1/2" -14 NPT	22	22
W45 AN 08 HN	1/2" -14 NPT	1/2" -14 NPT	22	25
W45 AN 08 HN 12	1/2" -14 NPT	3/4" -14 NPT	27	25
W45 AN 12 HN	3/4" -14 NPT	3/4" -14 NPT	27	32
W45 AN 12 HN 16	3/4" -14 NPT	1" -11.5 NPT	33	32
W45 AN 16 HN 12	1" -11.5 NPT	3/4" -14 NPT	33	38
W45 AN 16 HN	1" -11.5 NPT	1" -11.5 NPT	33	38
W45 AN 20 HN	1.1/4" -11.5 NPT	1.1/4" -11.5 NPT	41	48
W45 AN 24 HN	1.1/2" -11.5 NPT	1.1/2" -11.5 NPT	48	54
W45 AN 32 HN	2" -11.5 NPT	2" -11.5 NPT	64	67

SW, S1, S2 = With across flats

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.