
# W45 HRO HJ

Screw-in socket, angle 45°

## Properties

| | |
|---|---|
| **Connection 1** | BSP external thread, cylindrical |
| **Sealing form 1** | form G |
| **Connection 2** | UN/UNF external threads |
| **Sealing form 2** | 74° outer cone |
| **Design** | Adjustable direction screw-in socket |
| **Construction** | Angle 45° |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Item

| Identification | G1 | G2 | AF (mm) | S1 | OR |
|---|---|---|---|---|---|
| **W45 HRO 02 HJ 05** | G 1/8" -28 | 1/2"-20 UNF | 13 | 14 | 8.00 x 2.00 |
| **W45 HRO 04 HJ** | G 1/4" -19 | 7/16"-20 UNF | 14 | 19 | 10.77 x 2.62 |
| **W45 HRO 04 HJ 05** | G 1/4" -19 | 1/2"-20 UNF | 14 | 19 | 10.77 x 2.62 |
| **W45 HRO 04 HJ 08** | G 1/4" -19 | 3/4"-16 UNF | 19 | 19 | 10.77 x 2.62 |
| **W45 HRO 06 HJ 04** | G 3/8" -19 | 7/16"-20 UNF | 19 | 22 | 13.94 x 2.62 |
| **W45 HRO 06 HJ 05** | G 3/8" -19 | 1/2"-20 UNF | 19 | 22 | 13.94 x 2.62 |
| **W45 HRO 06 HJ** | G 3/8" -19 | 9/16"-18 UNF | 19 | 22 | 13.94 x 2.62 |
| **W45 HRO 06 HJ 10** | G 3/8" -19 | 7/8"-14 UNF | 22 | 22 | 13.94 x 2.62 |
| **W45 HRO 08 HJ 04** | G 1/2" -14 | 7/16"-20 UNF | 22 | 27 | 17.86 x 2.62 |
| **W45 HRO 08 HJ 06** | G 1/2" -14 | 9/16"-18 UNF | 22 | 27 | 17.86 x 2.62 |
| **W45 HRO 08 HJ** | G 1/2" -14 | 3/4"-16 UNF | 22 | 27 | 17.86 x 2.62 |
| **W45 HRO 08 HJ 12** | G 1/2" -14 | 1.1/16" -12 UN | 27 | 27 | 17.86 x 2.62 |
| **W45 HRO 12 HJ 08** | G 3/4" -14 | 3/4"-16 UNF | 27 | 36 | 23.47 x 2.62 |
| **W45 HRO 12 HJ 10** | G 3/4" -14 | 7/8"-14 UNF | 27 | 36 | 23.47 x 2.62 |
| **W45 HRO 24 HJ** | G 1.1/2" -11 | 1.7/8" -12 UN | 48 | 55 | 44.04 x 3.53 |

SW, S1, S2 = With across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*