

# W45 O HJOF

Screw-in socket, angle 45°

## Properties

|                       |                                      |
|-----------------------|--------------------------------------|
| <b>Connection 1</b>   | UN/UNF external threads              |
| <b>Sealing form 1</b> | O-ring seal on screw-in socket       |
| <b>Connection 2</b>   | ORFS external threads                |
| <b>Sealing form 2</b> | flat seal with O-ring                |
| <b>Design</b>         | Adjustable direction screw-in socket |
| <b>Construction</b>   | Angle 45°                            |
| <b>Material</b>       | Steel                                |
| <b>Surface</b>        | electro galvanised                   |



## Item

| Identification   | G1             | G2              | AF (mm) | S1 | OR1          | OR2          |
|------------------|----------------|-----------------|---------|----|--------------|--------------|
| W45 O 04 HJOF    | 7/16"-20 UNF   | 9/16"-18 UNF    | 14      | 16 | 8.92 x 1.83  | 7.65 x 1.78  |
| W45 O 04 HJOF 06 | 7/16"-20 UNF   | 11/16" -16 UN   | 19      | 16 | 8.92 x 1.83  | 9.25 x 1.78  |
| W45 O 06 HJOF 04 | 9/16"-18 UNF   | 9/16"-18 UNF    | 19      | 19 | 11.89 x 1.98 | 7.65 x 1.78  |
| W45 O 06 HJOF    | 9/16"-18 UNF   | 11/16" -16 UN   | 19      | 19 | 11.89 x 1.98 | 9.25 x 1.78  |
| W45 O 06 HJOF 08 | 9/16"-18 UNF   | 13/16" -16 UN   | 19      | 19 | 11.89 x 1.98 | 12.42 x 1.78 |
| W45 O 08 HJOF 06 | 3/4"-16 UNF    | 11/16" -16 UN   | 19      | 24 | 16.36 x 2.21 | 12.42 x 1.78 |
| W45 O 08 HJOF    | 3/4"-16 UNF    | 13/16" -16 UN   | 19      | 24 | 16.36 x 2.21 | 12.42 x 1.78 |
| W45 O 08 HJOF 10 | 3/4"-16 UNF    | 1" -14 UNS      | 27      | 24 | 16.36 x 2.21 | 15.60 x 1.78 |
| W45 O 10 HJOF 08 | 7/8" -14 UNF   | 13/16" -16 UN   | 27      | 27 | 19.18 x 2.46 | 12.42 x 1.78 |
| W45 O 10 HJOF    | 7/8" -14 UNF   | 1" -14 UNS      | 27      | 27 | 19.18 x 2.46 | 15.60 x 1.78 |
| W45 O 10 HJOF 12 | 7/8" -14 UNF   | 1.3/16" -12 UN  | 30      | 27 | 19.18 x 2.46 | 18.77 x 1.78 |
| W45 O 12 HJOF 10 | 1.1/16" -12 UN | 1" -14 UNS      | 30      | 36 | 23.47 x 2.95 | 15.60 x 1.78 |
| W45 O 12 HJOF    | 1.1/16" -12 UN | 1.3/16" -12 UN  | 30      | 35 | 23.47 x 2.95 | 18.77 x 1.78 |
| W45 O 12 HJOF 16 | 1.1/16" -12 UN | 1.7/16" -12 UN  | 36      | 36 | 23.47 x 2.95 | 23.52 x 1.78 |
| W45 O 16 HJOF 12 | 1.5/16" -12 UN | 1.3/16" -12 UN  | 37      | 41 | 29.74 x 2.95 | 18.77 x 1.78 |
| W45 O 16 HJOF    | 1.5/16" -12 UN | 1.7/16" -12 UN  | 37      | 41 | 29.74 x 2.95 | 23.52 x 1.78 |
| W45 O 20 HJOF 16 | 1.5/8" -12 UN  | 1.7/16" -12 UN  | 41      | 48 | 37.47 x 3.00 | 23.52 x 1.78 |
| W45 O 20 HJOF    | 1.5/8" -12 UN  | 1.11/16" -12 UN | 41      | 48 | 37.47 x 3.00 | 29.87 x 1.78 |
| W45 O 24 HJOF 20 | 1.7/8" -12 UN  | 1.11/16" -12 UN | 48      | 54 | 43.69 x 3.00 | 29.87 x 1.78 |
| W45 O 24 HJOF    | 1.7/8" -12 UN  | 2" -12 UN       | 48      | 54 | 43.69 x 3.00 | 37.82 x 1.78 |

SW, S1, S2 = With across flats

## Product versions

W45 O HJOF VA Screw-in socket, angle 45°, Stainless steel