


W90 AN HN

Screw-in socket, angle 90°

Properties

Connection 1	NPT nut thread (NPSM)
Sealing form 1	60° outer cone
Connection 2	NPT external threads
Sealing form 2	thread seal
Design	Screw-in sockets
Construction	Angle 90°
Material	Steel
Surface	electro galvanised



Item				
Identification	G1	G2	AF (mm)	S1
W90 AN 02 HN	1/8" -27 NPT	1/8" -27 NPT	11	14
W90 AN 04 HN 02	1/4" -18 NPT	1/8" -27 NPT	14	18
W90 AN 04 HN	1/4" -18 NPT	1/4" -18 NPT	14	18
W90 AN 04 HN 06	1/4" -18 NPT	3/8" -18 NPT	19	18
W90 AN 04 HN 08	1/4" -18 NPT	1/2" -14 NPT	19	18
W90 AN 06 HN 04	3/8" -18 NPT	1/4" -18 NPT	19	22
W90 AN 06 HN	3/8" -18 NPT	3/8" -18 NPT	19	22
W90 AN 06 HN 08	3/8" -18 NPT	1/2" -14 NPT	22	22
W90 AN 06 HN 12	3/8" -18 NPT	3/4" -14 NPT	25	22
W90 AN 08 HN 06	1/2" -14 NPT	3/8" -18 NPT	22	25
W90 AN 08 HN	1/2" -14 NPT	1/2" -14 NPT	22	25
W90 AN 08 HN 12	1/2" -14 NPT	3/4" -14 NPT	27	25
W90 AN 12 HN 08	3/4" -14 NPT	1/2" -14 NPT	27	32
W90 AN 12 HN	3/4" -14 NPT	3/4" -14 NPT	27	32
W90 AN 12 HN 16	3/4" -14 NPT	1" -11.5 NPT	33	32
W90 AN 16 HN 12	1" -11.5 NPT	3/4" -14 NPT	33	38
W90 AN 16 HN	1" -11.5 NPT	1" -11.5 NPT	33	38
W90 AN 20 HN	1.1/4" -11.5 NPT	1.1/4" -11.5 NPT	41	48
W90 AN 20 HN 24	1.1/4" -11.5 NPT	1.1/2" -11.5 NPT	48	48
W90 AN 24 HN	1.1/2" -11.5 NPT	1.1/2" -11.5 NPT	48	54
W90 AN 32 HN	2" -11.5 NPT	2" -11.5 NPT	64	67

SW, S1, S2 = With across flats