

# W90 HN HJ

Screw-in socket, angle 90°

**HANSA FLEX**

## Properties

Connection 1	NPT external threads
Sealing form 1	thread seal
Connection 2	UN/UNF external threads
Sealing form 2	74° outer cone
Design	Screw-in sockets
Construction	Angle 90°
Material	Steel
Surface	electro galvanised



## Item

Identification	G1	G2	AF (mm)
W90 HN 02 HJ	1/8" -27 NPT	5/16" -24 UN	8
W90 HN 02 HJ 04	1/8" -27 NPT	7/16"-20 UNF	11
W90 HN 02 HJ 05	1/8" -27 NPT	1/2"-20 UNF	13
W90 HN 02 HJ 06	1/8" -27 NPT	9/16"-18 UNF	14
W90 HN 04 HJ	1/4" -18 NPT	7/16"-20 UNF	14
W90 HN 04 HJ 05	1/4" -18 NPT	1/2"-20 UNF	14
W90 HN 04 HJ 06	1/4" -18 NPT	9/16"-18 UNF	14
W90 HN 04 HJ 08	1/4" -18 NPT	3/4"-16 UNF	19
W90 HN 06 HJ 04	3/8" -18 NPT	7/16"-20 UNF	19
W90 HN 06 HJ	3/8" -18 NPT	9/16"-18 UNF	19
W90 HN 06 HJ 05	3/8" -18 NPT	1/2"-20 UNF	19
W90 HN 06 HJ 08	3/8" -18 NPT	3/4"-16 UNF	19
W90 HN 06 HJ 10	3/8" -18 NPT	7/8"-14 UNF	22
W90 HN 08 HJ 04	1/2" -14 NPT	7/16"-20 UNF	22
W90 HN 08 HJ	1/2" -14 NPT	3/4"-16 UNF	22
W90 HN 08 HJ 05	1/2" -14 NPT	1/2"-20 UNF	19
W90 HN 08 HJ 06	1/2" -14 NPT	9/16"-18 UNF	22
W90 HN 08 HJ 10	1/2" -14 NPT	7/8"-14 UNF	22
W90 HN 08 HJ 12	1/2" -14 NPT	1.1/16" -12 UN	27
W90 HN 12 HJ	3/4" -14 NPT	1.1/16" -12 UN	27
W90 HN 12 HJ 06	3/4" -14 NPT	9/16"-18 UNF	27
W90 HN 12 HJ 08	3/4" -14 NPT	3/4"-16 UNF	27
W90 HN 12 HJ 10	3/4" -14 NPT	7/8"-14 UNF	27
W90 HN 12 HJ 14	3/4" -14 NPT	1.3/16" -12 UN	31
W90 HN 12 HJ 16	3/4" -14 NPT	1.5/16" -12 UN	33
W90 HN 16 HJ	1" -11.5 NPT	1.5/16" -12 UN	33
W90 HN 16 HJ 12	1" -11.5 NPT	1.1/16" -12 UN	33
W90 HN 16 HJ 20	1" -11.5 NPT	1.5/8" -12 UN	41
W90 HN 20 HJ 16	1.1/4" -11.5 NPT	1.5/16" -12 UN	45
W90 HN 20 HJ	1.1/4" -11.5 NPT	1.5/8" -12 UN	45
W90 HN 20 HJ 24	1.1/4" -11.5 NPT	1.7/8" -12 UN	48
W90 HN 24 HJ 20	1.1/2" -11.5 NPT	1.5/8" -12 UN	48
W90 HN 24 HJ	1.1/2" -11.5 NPT	1.7/8" -12 UN	48
W90 HN 32 HJ	2" -11.5 NPT	2.1/2" -12 UN	64

AF = Width across flats

## Product versions

W90 HN HJ VA Screw-in socket, angle 90°, Stainless steel