
# W90 HN HJ VA

Screw-in socket, angle 90°

## Properties

| | |
|---|---|
| **Connection 1** | NPT external threads |
| **Sealing form 1** | thread seal |
| **Connection 2** | UN/UNF external threads |
| **Sealing form 2** | 74° outer cone |
| **Design** | Screw-in sockets |
| **Construction** | Angle 90° |
| **Material** | Stainless steel |






## Item

| Identification | G1 | G2 | AF (mm) | S1 |
|---|---|---|---|---|
| **W90 HN 06 HJ 05 VA** | 3/8" -18 NPT | 1/2"-20 UNF | 19 | - |
| **W90 HN 20 HJ 24 VA** | 1.1/4" -11.5 NPT | 1.7/8" -12 UN | 48 | - |
| **W90 HN 02 HJ 04 VA** | 1/8" -27 NPT | 7/16"-20 UNF | 11 | - |
| **W90 HN 02 HJ 05 VA** | 1/8" -27 NPT | 1/2"-20 UNF | 13 | - |
| **W90 HN 02 HJ 06 VA** | 1/8" -27 NPT | 9/16"-18 UNF | 14 | - |
| **W90 HN 04 HJ VA** | 1/4" -18 NPT | 7/16"-20 UNF | 14 | - |
| **W90 HN 04 HJ 05 VA** | 1/4" -18 NPT | 1/2"-20 UNF | 14 | - |
| **W90 HN 04 HJ 06 VA** | 1/4" -18 NPT | 9/16"-18 UNF | 14 | - |
| **W90 HN 04 HJ 08 VA** | 1/4" -18 NPT | 3/4"-16 UNF | 19 | - |
| **W90 HN 06 HJ 04 VA** | 3/8" -18 NPT | 7/16"-20 UNF | 19 | - |
| **W90 HN 06 HJ VA** | 3/8" -18 NPT | 9/16"-18 UNF | 19 | - |
| **W90 HN 06 HJ 08 VA** | 3/8" -18 NPT | 3/4"-16 UNF | 19 | - |
| **W90 HN 08 HJ 16 VA** | 1/2" -14 NPT | 1.5/16" -12 UN | 33 | 24 |
| **W90 HN 06 HJ 10 VA** | 3/8" -18 NPT | 7/8"-14 UNF | 22 | - |
| **W90 HN 08 HJ VA** | 1/2" -14 NPT | 3/4"-16 UNF | 22 | - |
| **W90 HN 08 HJ 06 VA** | 1/2" -14 NPT | 9/16"-18 UNF | 22 | - |
| **W90 HN 08 HJ 10 VA** | 1/2" -14 NPT | 7/8"-14 UNF | 22 | - |
| **W90 HN 08 HJ 12 VA** | 1/2" -14 NPT | 1.1/16" -12 UN | 27 | - |
| **W90 HN 12 HJ VA** | 3/4" -14 NPT | 1.1/16" -12 UN | 27 | - |
| **W90 HN 12 HJ 10 VA** | 3/4" -14 NPT | 7/8"-14 UNF | 27 | - |
| **W90 HN 12 HJ 16 VA** | 3/4" -14 NPT | 1.5/16" -12 UN | 33 | - |
| **W90 HN 16 HJ VA** | 1" -11.5 NPT | 1.5/16" -12 UN | 33 | - |
| **W90 HN 16 HJ 12 VA** | 1" -11.5 NPT | 1.1/16" -12 UN | 33 | - |
| **W90 HN 16 HJ 20 VA** | 1" -11.5 NPT | 1.5/8" -12 UN | 41 | - |
| **W90 HN 20 HJ VA** | 1.1/4" -11.5 NPT | 1.5/8" -12 UN | 45 | - |
| **W90 HN 24 HJ VA** | 1.1/2" -11.5 NPT | 1.7/8" -12 UN | 48 | - |

AF = Width across flats

## Product versions

| | |
|---|---|
| **W90 HN HJ** | Screw-in socket, angle 90°, Steel |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*