# W90 HRK AB


Screw-in socket, angle 90°

HANSA-FLEX

## Properties

| | |
|---|---|
| **Connection 1** | BSPT conical external threads |
| **Sealing form 1** | thread seal |
| **Connection 2** | BSP nut thread |
| **Sealing form 2** | 60° inner cone |
| **Design** | Screw-in sockets |
| **Construction** | Angle 90° |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Item

| Identification | G1 | G2 | AF (mm) | S1 | S2 |
|---|---|---|---|---|---|
| **W90 HRK 04 AB** | R 1/4" K | G 1/4" -19 | 14 | 19 | 19 |
| **W90 HRK 06 AB** | R 3/8" K | G 3/8" -19 | 19 | 22 | 22 |
| **W90 HRK 08 AB** | R 1/2" K | G 1/2" -14 | 22 | 27 | 27 |
| **W90 HRK 12 AB** | R 3/4" K | G 3/4" -14 | 27 | 32 | 32 |
| **W90 HRK 16 AB** | R 1" K | G 1" -11 | 33 | 41 | 41 |
| **W90 HRK 20 AB** | R 1.1/4" K | G 1.1/4" -11 | 41 | 50 | 50 |
| **W90 HRK 24 AB** | R 1.1/2" K | G 1.1/2" -11 | 48 | 60 | 60 |

SW, S1, S2 = With across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*