


Properties			
Connection 1	BSPT conical external threads		
Sealing form 1	thread seal		
Connection 2	BSP cylindrical external threads		
Sealing form 2	60° inner cone		
Design	Screw-in sockets		
Construction	Angle 90°		
Material	Steel		
Surface	electro galvanised		





Item				
Identification	G1	G2	AF (mm)	
W90 HRK 02 HB	R 1/8" K	G 1/8" -28	11	
W90 HRK 02 HB 04	R 1/8" K	G 1/4" -19	11	
W90 HRK 04 HB 02	R 1/4" K	G 1/8" -28	14	
W90 HRK 04 HB	R 1/4" K	G 1/4" -19	14	
W90 HRK 04 HB 06	R 1/4" K	G 3/8" -19	14	
W90 HRK 06 HB 04	R 3/8" K	G 1/4" -19	14	
W90 HRK 06 HB	R 3/8" K	G 3/8" -19	17	
W90 HRK 06 HB 08	R 3/8" K	G 1/2" -14	19	
W90 HRK 08 HB 06	R 1/2" K	G 3/8" -19	19	
W90 HRK 08 HB	R 1/2" K	G 1/2" -14	19	
W90 HRK 08 HB 12	R 1/2" K	G 3/4" -14	27	
W90 HRK 12 HB 08	R 3/4" K	G 1/2" -14	27	
W90 HRK 12 HB	R 3/4" K	G 3/4" -14	27	
W90 HRK 12 HB 16	R 3/4" K	G 1" -11	33	
W90 HRK 16 HB 12	R 1" K	G 3/4" -14	33	
W90 HRK 16 HB	R 1" K	G 1" -11	36	
W90 HRK 20 HB	R 1.1/4" K	G 1.1/4" -11	41	
W90 HRK 24 HB	R 1.1/2" K	G 1.1/2" -11	48	
W90 HRK 32 HB	R 2" K	G 2" -11	64	

AF = Width across flats