W90 O HB


Screw-in socket, AGR, angle 90°

HANSA-FLEX

Properties

Connection 1	UN/UNF external threads
Sealing form 1	O-ring seal on screw-in socket
Connection 2	BSP cylindrical external threads
Sealing form 2	60° inner cone
Design	Screw-in sockets
Construction	Angle 90°
Material	Steel
Surface	electro galvanised





Item

Identification	G1	G2	AF (mm)	S1	OR
W90 O 04 HB 02	7/16"-20 UNF	G 1/8" -28	11	17	8.92 x 1.83
W90 O 04 HB	7/16"-20 UNF	G 1/4" -19	11	17	8.92 x 1.83
W90 O 04 HB 06	7/16"-20 UNF	G 3/8" -19	14	17	8.92 x 1.83
W90 O 05 HB 02	1/2"-20 UNF	G 1/8" -28	14	19	10.52 x 1.83
W90 O 05 HB 04	1/2"-20 UNF	G 1/4" -19	14	19	10.52 x 1.83
W90 O 06 HB 04	9/16"-18 UNF	G 1/4" -19	14	21	11.90 x 1.98
W90 O 06 HB	9/16"-18 UNF	G 3/8" -19	14	21	11.90 x 1.98
W90 O 08 HB 04	3/4"-16 UNF	G 1/4" -19	19	25	16.36 x 2.20
W90 O 08 HB 06	3/4"-16 UNF	G 3/8" -19	19	25	16.36 x 2.20
W90 O 08 HB	3/4"-16 UNF	G 1/2" -14	19	25	16.36 x 2.20
W90 O 08 HB 12	3/4"-16 UNF	G 3/4" -14	22	25	16.36 x 2.20
W90 O 10 HB 06	7/8" -14 UNF	G 3/8" -19	22	30	19.18 x 2.46
W90 O 10 HB 08	7/8" -14 UNF	G 1/2" -14	22	30	19.18 x 2.46
W90 O 10 HB	7/8" -14 UNF	G 5/8" -14	22	30	19.18 x 2.46
W90 O 10 HB 12	7/8" -14 UNF	G 3/4" -14	22	30	19.18 x 2.46
W90 O 12 HB 08	1.1/16" -12 UN	G 1/2" -14	27	36	23.47 x 2.95
W90 O 12 HB	1.1/16" -12 UN	G 3/4" -14	27	36	23.47 x 2.95
W90 O 12 HB 16	1.1/16" -12 UN	G 1" -11	33	36	23.47 x 2.95
W90 O 16 HB 12	1.5/16" -12 UN	G 3/4" -14	33	45	29.74 x 2.95
W90 O 16 HB	1.5/16" -12 UN	G 1" -11	33	45	29.74 x 2.95
W90 O 16 HB 20	1.5/16" -12 UN	G 1.1/4" -11	41	45	29.74 x 2.95
W90 O 20 HB 16	1.5/8" -12 UN	G 1" -11	41	55	37.47 x 3.00
W90 O 20 HB	1.5/8" -12 UN	G 1.1/4" -11	41	55	37.47 x 3.00

SW, S1, S2 = With across flats

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.