
# W90 O HJ

Screw-in socket, AGJ, angle 90°

## Properties

| | |
|---|---|
| **Connection 1** | UN/UNF external threads |
| **Sealing form 1** | O-ring seal on screw-in socket |
| **Connection 2** | UN/UNF external threads |
| **Sealing form 2** | 74° outer cone |
| **Design** | Adjustable direction screw-in socket |
| **Construction** | Angle 90° |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Item

| Identification | G1 | G2 | AF (mm) | S1 | OR |
|---|---|---|---|---|---|
| **W90 O 04 HJ** | 7/16"-20 UNF | 7/16"-20 UNF | 12 | 14 | 9.17 x 1.63 |
| **W90 O 04 HJ 05** | 7/16"-20 UNF | 1/2"-20 UNF | 12 | 14 | 9.17 x 1.63 |
| **W90 O 04 HJ 06** | 7/16"-20 UNF | 9/16"-18 UNF | 12 | 14 | 9.17 x 1.63 |
| **W90 O 05 HJ 04** | 1/2"-20 UNF | 7/16"-20 UNF | 13 | 17 | 10.52 x 1.83 |
| **W90 O 05 HJ** | 1/2"-20 UNF | 1/2"-20 UNF | 13 | 17 | 10.52 x 1.83 |
| **W90 O 05 HJ 06** | 1/2"-20 UNF | 9/16"-18 UNF | 13 | 17 | 10.52 x 1.83 |
| **W90 O 06 HJ 04** | 9/16"-18 UNF | 7/16"-20 UNF | 14 | 17 | 11.90 x 1.98 |
| **W90 O 06 HJ 05** | 9/16"-18 UNF | 1/2"-20 UNF | 14 | 17 | 11.90 x 1.98 |
| **W90 O 06 HJ** | 9/16"-18 UNF | 9/16"-18 UNF | 14 | 17 | 11.90 x 1.98 |
| **W90 O 06 HJ 08** | 9/16"-18 UNF | 3/4"-16 UNF | 14 | 17 | 11.90 x 1.98 |
| **W90 O 08 HJ** | 3/4"-16 UNF | 3/4"-16 UNF | 19 | 22 | 16.36 x 2.20 |
| **W90 O 08 HJ 06** | 3/4"-16 UNF | 9/16"-18 UNF | 19 | 22 | 16.36 x 2.20 |
| **W90 O 08 HJ 10** | 3/4"-16 UNF | 7/8"-14 UNF | 19 | 22 | 16.36 x 2.20 |
| **W90 O 08 HJ 12** | 3/4"-16 UNF | 1.1/16" -12 UN | 19 | 22 | 16.36 x 2.20 |
| **W90 O 10 HJ 08** | 7/8" -14 UNF | 3/4"-16 UNF | 22 | 27 | 19.18 x 2.46 |
| **W90 O 10 HJ 06** | 7/8" -14 UNF | 9/16"-18 UNF | 22 | 27 | 19.18 x 2.46 |
| **W90 O 10 HJ** | 7/8" -14 UNF | 7/8"-14 UNF | 22 | 27 | 19.18 x 2.46 |
| **W90 O 10 HJ 12** | 7/8" -14 UNF | 1.1/16" -12 UN | 22 | 27 | 19.18 x 2.46 |
| **W90 O 12 HJ 08** | 1.1/16" -12 UN | 3/4"-16 UNF | 27 | 32 | 23.47 x 2.95 |
| **W90 O 12 HJ** | 1.1/16" -12 UN | 1.1/16" -12 UN | 27 | 32 | 23.47 x 2.95 |
| **W90 O 12 HJ 16** | 1.1/16" -12 UN | 1.5/16" -12 UN | 27 | 32 | 23.47 x 2.95 |
| **W90 O 12 HJ 10** | 1.1/16" -12 UN | 7/8"-14 UNF | 27 | 32 | 23.47 x 2.95 |
| **W90 O 16 HJ** | 1.5/16" -12 UN | 1.5/16" -12 UN | 33 | 41 | 29.74 x 2.95 |
| **W90 O 16 HJ 12** | 1.5/16" -12 UN | 1.1/16" -12 UN | 33 | 41 | 29.74 x 2.95 |
| **W90 O 16 HJ 20** | 1.5/16" -12 UN | 1.5/8" -12 UN | 33 | 41 | 29.74 x 2.95 |
| **W90 O 20 HJ 16** | 1.5/8" -12 UN | 1.5/16" -12 UN | 41 | 50 | 37.47 x 3.00 |
| **W90 O 20 HJ** | 1.5/8" -12 UN | 1.5/8" -12 UN | 41 | 50 | 37.47 x 3.00 |
| **W90 O 24 HJ** | 1.7/8" -12 UN | 1.7/8" -12 UN | 48 | 55 | 43.69 x 3.00 |
| **W90 O 32 HJ** | 2.1/2" -12 UN | 2.1/2" -12 UN | 65 | 70 | 59.36 x 3.00 |

SW, S1, S2 = With across flats

## Product versions

| | |
|---|---|
| **W90 O HJ VA** | Screw-in socket, AGJ, angle 90°, Stainless steel |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*