


Properties				
Connection 1	metric nut thread			
Sealing form 1	24° outer cone with O-ring			
Connection 2	metric cylindrical outer thread			
Sealing form 2	24° inner cone			
Design	Connecting socket (short pipe bend)			
Construction	Angle 45°			
Material	Steel			
Surface	electro galvanised			





## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item								
Identification	Series	External pipe Ø	Calculation pressure	G1 + G2	S1	S2	OR	
WB45 AOS 03 HS	S	6	600	M 14 x 1.5	17	14	4.0 x 1.5	
WB45 AOS 04 HS	S	8	600	M 16 x 1.5	19	17	6.0 x 1.5	
WB45 AOS 06 HS	S	10	600	M 18 x 1.5	22	19	7.5 x 1.5	
WB45 AOS 08 HS	S	12	600	M 20 x 1.5	24	22	9.0 x 1.5	
WB45 AOS 10 HS	S	14	600	M 22 x 1.5	27	22	10.0 x 2.0	
WB45 AOS 13 HS	S	16	400	M 24 x 1.5	30	24	12.0 x 2.0	
WB45 AOS 16 HS	S	20	400	M 30 x 2	36	30	16.3 x 2.4	
WB45 AOS 20 HS	S	25	400	M 36 x 2	46	36	20.3 x 2.4	
WB45 AOS 25 HS	S	30	400	M 42 x 2	50	46	25.3 x 2.4	
WB45 AOS 32 HS	S	38	315	M 52 x 2	60	55	33.3 x 2.4	

Series: LL = Very light L = Light S = Heavy - SW, S1, S2 = With across flats