


Properties				
Connection 1	metric nut thread			
Sealing form 1	24° outer cone with O-ring			
Connection 2	metric nut thread			
Sealing form 2	24° outer cone with O-ring			
Design	Connecting socket (short pipe bend)			
Construction	Angle 45°			
Material	Steel			
Surface	electro galvanised			





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe

Item								
Identification	Series	External pipe Ø	Calculation pressure	G1 + G2	S1	S2	OR1 + OR2	
WB45 NW 03 AOS	S	6	600	M 14 x 1.5	17	17	4.0 x 1.5	
WB45 NW 04 AOS	S	8	600	M 16 x 1.5	19	19	6.0 x 1.5	
WB45 NW 06 AOS	S	10	600	M 18 x 1.5	22	22	7.5 x 1.5	
WB45 NW 08 AOS	S	12	600	M 20 x 1.5	24	24	9.0 x 1.5	
WB45 NW 10 AOS	S	14	600	M 22 x 1.5	27	27	10.0 x 2.0	
WB45 NW 13 AOS	S	16	400	M 24 x 1.5	30	30	12.0 x 2.0	
WB45 NW 16 AOS	S	20	400	M 30 x 2	36	36	16.3 x 2.4	
WB45 NW 20 AOS	S	25	400	M 36 x 2	46	46	20.3 x 2.4	
WB45 NW 25 AOS	S	30	400	M 42 x 2	50	50	25.3 x 2.4	
WB45 NW 32 AOS	S	38	315	M 52 x 2	60	60	33.2 x 2.4	

Series: LL = Very light L = Light S = Heavy - SW, S1, S2 = With across flats