


Properties					
Connection 1	metric nut thread				
Sealing form 1	24° outer cone with O-ring				
Connection 2	metric cylindrical outer thread				
Sealing form 2	24° inner cone				
Design	Connecting socket (short pipe bend)				
Construction	Angle 90°				
Material	Steel				
Surface	electro galvanised				





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item							
Identification	Series	External pipe Ø	Calculation pressure	G1 + G2	S1	S2	OR
WB90 AOS 03 HS	S	6	600	M 14 x 1.5	17	14	4.0 x 1.5
WB90 AOS 04 HS	S	8	600	M 16 x 1.5	19	17	6.0 x 1.5
WB90 AOS 06 HS	S	10	600	M 18 x 1.5	22	19	7.5 x 1.5
WB90 AOS 08 HS	S	12	600	M 20 x 1.5	24	22	9.0 x 1.5
WB90 AOS 10 HS	S	14	600	M 22 x 1.5	27	22	10.0 x 2.0
WB90 AOS 13 HS	S	16	400	M 24 x 1.5	30	24	12.0 x 2.0
WB90 AOS 16 HS	S	20	400	M 30 x 2	36	30	16.3 x 2.4
WB90 AOS 20 HS	S	25	400	M 36 x 2	46	36	20.3 x 2.4
WB90 AOS 25 HS	S	30	400	M 42 x 2	50	46	25.3 x 2.4
WB90 AOS 32 HS	S	38	360	M 52 x 2	60	55	33.3 x 2.4

Series: LL = Very light L = Light S = Heavy - SW, S1, S2 = With across flats