


### Properties

<b>Connection 1 - 3</b>	metric cylindrical outer thread
<b>Sealing form 1 - 3</b>	24° inner cone
<b>Construction</b>	T shaped
<b>Design</b>	Shuttle valve, connector
<b>Scope of supply</b>	Socket (without union nut and cutting ring)
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

### Description

With two lockable inlets and one outlet.

### Item

Identification	Series	Operating pressure	Ø d2 (mm)	M	Ø d (mm)	L4 (mm)	L7 (mm)	S1
XWV NW 06 HL	L	PN 160	8	M 14 x 1.5	4,5	14,0	21	14
XWV NW 08 HL	L	PN 160	10	M 16 x 1.5	6,0	15,0	22	17
XWV NW 10 HL	L	PN 160	12	M 18 x 1.5	7,5	17,0	24	19
XWV NW 13 HL	L	PN 160	15	M 22 x 1.5	10,0	21,0	28	19
XWV NW 03 HS	S	PN 400	6	M 14 x 1.5	3,0	16,0	24	14
XWV NW 04 HS	S	PN 400	8	M 16 x 1.5	4,5	17,0	24	17
XWV NW 06 HS	S	PN 400	10	M 18 x 1.5	6,0	17,5	25	19
XWV NW 13 HS	S	PN 400	16	M 24 x 1.5	7,5	21,5	30	22

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

### Product versions

WV Shuttle valve, connector, Socket with union nut and cutting ring