


# AFS SCHRAUBE

Hexagon socket screw

## Properties

<b>Design</b>	Hexagon socket screw
<b>Standard</b>	DIN 912 (ISO 4762)
<b>Material</b>	Steel 10.9
<b>Surface</b>	black oiled



## Item

Identification	G1	L1 (mm)	AF (mm)
<b>AFS SCHRAUBE 1</b>	M 8 x 1.25	25	6
<b>AFS SCHRAUBE 2</b>	M 8 x 1.25	30	6
<b>AFS SCHRAUBE 3</b>	M 10 x 1.5	35	8
<b>AFS SCHRAUBE 4</b>	M 10 x 1.5	40	8
<b>AFS SCHRAUBE 5</b>	M 12 x 1.75	45	10
<b>AFS SCHRAUBE 6</b>	M 14 x 2	45	12
<b>AFS SCHRAUBE 7</b>	M 16 x 2	50	14
<b>AFS SCHRAUBE 8</b>	M 20 x 2.5	65	17

AF = Width across flats

## Accessory for following products

<b>FH (3000 PSI)</b>	SAE flange half
<b>FH (6000 PSI)</b>	SAE flange half
<b>VF (3000 PSI)</b>	SAE full flange
<b>VF (6000 PSI)</b>	SAE full flange