


| Properties | | | | | | |
|-----------------|----------------------------------|--|--|--|--|--|
| Design | Pump connection (4 hole) | | | | | |
| Construction | straight | | | | | |
| Mounting | with metric screw set | | | | | |
| Scope of supply | with metric screw set and O-ring | | | | | |
| Material | Steel ST 42.3 | | | | | |
| Surface | electro galvanised | | | | | |





Note

The stated maximum working pressure relates to the flange. The actual working pressure is determined by the pipe (wall thickness) and the quality of the pipe.

| Item | | | | | | | | | | | | |
|----------------|----------------------|------------|------------|-------------|-----------|-----------|-----------|-----------|-----------------|--------------|--|--|
| Identification | Pressure PB (bar) | LK (mm) | A1 (mm) | Ø B (mm) | D (mm) | G (mm) | H (mm) | L (mm) | Screws | OR | | |
| FB 1 | 250 | 30 | 19,0 | 14,0 | 45 | 55 | 10 | 6,5 | (4 x) M 6 x 20 | 18.77 x 1.78 | | |
| FB 2 | 250 | 40 | 25,4 | 19,0 | 58 | 60 | 12 | 8,5 | (4 x) M 8 x 25 | 25.12 x 1.78 | | |
| FB 3 B | 250 | 56 | 32,0 | 24,5 | 76 | 72 | 16 | 10,5 | (4 x) M 10 x 35 | 31.42 x 2.62 | | |

PN = Nominal pressure PB = Max. operating pressure