
## HANSA/FLEX

| Properties   |                          |
|--------------|--------------------------|
| Design       | Cetop square flange      |
| Construction | straight                 |
| Standard     | CETOP RP 63H<br>ISO 6164 |
| Material     | S355J2G3 (ST52.3)        |
| Surface      | black oiled              |





## Item

| Identification   | Pressure PB<br>(bar) | Size   | A<br>(mm) | ØB<br>(mm) | C<br>(mm) | D<br>(mm) | E<br>(mm) |
|------------------|----------------------|--------|-----------|------------|-----------|-----------|-----------|
|                  |                      |        |           |            |           |           |           |
| G VKS 12 ST 250  | 250                  | 1/2"   | 22        | 15,0       | 30,2      | 24,0      | 30        |
| G VKS 34 ST 250  | 250                  | 3/4"   | 28        | 20,0       | 38,1      | 31,5      | 35        |
| G VKS 1 ST 250   | 250                  | 1"     | 35        | 25,0       | 44,4      | 38,0      | 40        |
| G VKS 114 ST 250 | 250                  | 1.1/4" | 43        | 32,0       | 50,8      | 43,0      | 45        |
| G VKS 112 ST 250 | 250                  | 1.1/2" | 50        | 38,0       | 60,3      | 50,0      | 50        |
| G VKS 2 ST 250   | 250                  | 2"     | 62        | 47,0       | 71,4      | 62,0      | 60        |
| G VKS 212 ST 250 | 250                  | 2.1/2" | 76        | 58,0       | 87,2      | 76,0      | 70        |
| G VKS 3 ST 250   | 250                  | 3"     | 90        | 70,0       | 101,6     | 90,0      | 80        |
| G VKS 312 ST 250 | 250                  | 3.1/2" | 102       | 80,0       | 119,0     | 102,0     | 90        |
| G VKS 4 ST 250   | 250                  | 4"     | 114       | 90,0       | 131,0     | 114,0     | 105       |

PN = Nominal pressure PB = Max. operating pressure - Series: LL = Very light L = Light S = Heavy