GFC S (3000 PSI)


SAE socket weld counter flange, ND 40

HANSA-FLEX

Properties

Pressure series	3000 psi
Standard	SAE J 518 C ISO 6162
Construction type	ND 40
Construction	straight
Design	SAE socket weld counter flange
Mounting	Inner thread for metric screws
Material	S355J2G3 (ST52.3)
Surface	black oiled





Note

The stated maximum working pressure relates to the flange. The actual working pressure is determined by the pipe (wall thickness) and the quality of the pipe.

Item

Identification	PB 10.9 (bar)	Size	Pipe	A (mm)	Ø B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	I (mm)	M metr.
GFC 80 S	40	1/2"	22 x 2	22,5	15	38,1	56	17,5	46	10	3	M 8
GFC 100 S	40	3/4"	28 x 2	28,5	20	47,6	65	22,2	50	12	4	M 10
GFC 102 S	40	1"	35 x 2	35,5	29	52,4	70	26,2	55	12	4	M 10
GFC 104 S	40	1.1/4"	42 x 2	42,5	34	58,7	79	30,2	68	12	4	M 10
GFC 106 S	40	1.1/2"	48.3 x 3.25	42,0	42	69,9	93	35,7	78	15	4	M 12
GFC 108 S	40	2"	60.3 x 3.65	61,0	53	77,8	102	42,9	90	15	4	M 12
GFC 110 S	40	2.1/2"	76.1 x 3.65	77,0	64	88,9	114	50,8	105	15	4	M 12
GFC 112 S	40	3"	88.9 x 4.05	90,0	80	106,4	134	61,9	124	20	5	M 16
GFC 114 S	35	3.1/2"	101.6 x 4.5	103,0	93	120,7	152	69,9	136	20	5	M 16
GFC 116 S	35	4"	114.3 x 4.5	116,0	105	130,2	162	77,8	146	25	6	M 16
GFC 118 S	35	5"	139.7 x 4.85	141,0	126	152,4	190	92,1	170	28	8	M 16

PN = Nominal pressure PB = Max. operating pressure

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.