

WF LK 3 M

Pump connection (3 hole), angle 90°

HANSA FLEX

Properties

| | |
|------------------------|----------------------------------------------|
| Design | Pump connection (3 hole) |
| Construction | Angle 90° |
| Mounting | with metric screw set |
| Scope of supply | with screw set, O-ring, nut and cutting ring |
| Material | Malleable cast iron GTW 40 |
| Surface | electro galvanised |



Item

| Identification | Series | Ø RAD (mm) | Pressure PB (bar) | LK (mm) | A | D (mm) | S1 (mm) | S2 (mm) | S3 (mm) | L (mm) | Screws | OR |
|-------------------|--------|------------|-------------------|---------|---------|--------|---------|---------|---------|--------|----------------|------------|
| WF 30 LK L 12-3 M | L | 12 | 250 | 30 | M18x1,5 | 38 | 19 | 30,0 | 46,5 | 6,4 | (3 x) M 6 x 25 | 16.0 x 2.5 |
| WF 30 LK L 15-3 M | L | 15 | 250 | 30 | M22x1,5 | 38 | 19 | 30,0 | 46,0 | 6,4 | (3 x) M 6 x 25 | 16.0 x 2.5 |
| WF 40 LK L 22-3 M | L | 22 | 160 | 40 | M30x2 | 48 | 25 | 35,5 | 52,5 | 8,4 | (3 x) M 8 x 30 | 24.0 x 2.5 |
| WF 40 LK L 28-3 M | L | 28 | 160 | 40 | M36x2 | 48 | 25 | 35,5 | 52,5 | 8,4 | (3 x) M 8 x 30 | 24.0 x 2.5 |

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø RAD = External pipe diameter

Product versions

WF LK 3 Pump connection (3 hole), angle 90°, with metric screw set and O-ring