


Properties							
Design	Pump connection (3 hole)						
Construction	Angle 90°						
Mounting	with metric screw set						
Scope of supply	with screw set, O-ring, nut and cutting ring						
Material	Malleable cast iron GTW 40						
Surface	electro galvanised						





Item												
Identification	Series	Ø RAD	Pressure PB	LK	Α	D	S1	S2	S3	L	Screws	OR
		(mm)	(bar)	(mm)		(mm)	(mm)	(mm)	(mm)	(mm)		
WF 30 LK L 12-3 M	L	12	250	30	M18x1,5	38	19	30,0	46,5	6,4	(3 x) M 6 x 25	16.0 x 2.5
WF 30 LK L 15-3 M	L	15	250	30	M22x1,5	38	19	30,0	46,0	6,4	(3 x) M 6 x 25	16.0 x 2.5
WF 40 LK L 22-3 M	L	22	160	40	M30x2	48	25	35,5	52,5	8,4	(3 x) M 8 x 30	24.0 x 2.5
WF 40 LK L 28-3 M	L	28	160	40	M36x2	48	25	35,5	52,5	8,4	(3 x) M 8 x 30	24.0 x 2.5

Series: LL = Very light L = Light S = Heavy - PN = Nominal pressure PB = Max. operating pressure - Ø RAD = External pipe diameter

## **Product versions**

WF LK 3 Pump connection (3 hole), angle 90°, with metric screw set and O-ring