
# DMO 45
Fitting, double nuts, angle 45°

## Properties

| | |
|---|---|
| **Connection 1 + 2** | metric nut thread |
| **Sealing form 1 + 2** | 24° outer cone with O-ring |
| **Design** | Fitting, double nuts |
| **Construction** | Angle 45° |
| **Standard** | DIN 2353<br>ISO 8434-1 |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

| Identification | Series | Operating pressure | Ø d (mm) | G1 | L1 (mm) | AF (mm) | S1 | OR |
|---|---|---|---|---|---|---|---|---|
| **DMO 45 NW 04 L** | L | PN 400 | 6 | M 12 x 1.5 | 22,5 | 14 | 14 | 4.0 x 1.5 |
| **DMO 45 NW 06 L** | L | PN 400 | 8 | M 14 x 1.5 | 23,0 | 14 | 17 | 6.0 x 1.5 |
| **DMO 45 NW 08 L** | L | PN 400 | 10 | M 16 x 1.5 | 25,0 | 19 | 19 | 7.5 x 1.5 |
| **DMO 45 NW 10 L** | L | PN 400 | 12 | M 18 x 1.5 | 25,5 | 19 | 22 | 9.0 x 1.5 |
| **DMO 45 NW 13 L** | L | PN 400 | 15 | M 22 x 1.5 | 27,0 | 22 | 27 | 12.0 x 2.0 |
| **DMO 45 NW 16 L** | L | PN 315 | 18 | M 26 x 1.5 | 30,0 | 27 | 32 | 15.0 x 2.0 |
| **DMO 45 NW 20 L** | L | PN 315 | 22 | M 30 x 2 | 32,0 | 30 | 36 | 20.0 x 2.0 |
| **DMO 45 NW 25 L** | L | PN 250 | 28 | M 36 x 2 | 35,0 | 36 | 41 | 26.0 x 2.0 |
| **DMO 45 NW 32 L** | L | PN 250 | 35 | M 45 x 2 | 39,5 | 50 | 50 | 32.0 x 2.5 |
| **DMO 45 NW 40 L** | L | PN 250 | 42 | M 52 x 2 | 42,0 | 50 | 60 | 38.0 x 2.5 |
| **DMO 45 NW 03 S** | S | PN 630 | 6 | M 14 x 1.5 | 23,5 | 14 | 17 | 4.0 x 1.5 |
| **DMO 45 NW 04 S** | S | PN 630 | 8 | M 16 x 1.5 | 26,5 | 19 | 19 | 6.0 x 1.5 |
| **DMO 45 NW 06 S** | S | PN 630 | 10 | M 18 x 1.5 | 27,0 | 19 | 22 | 7.5 x 1.5 |
| **DMO 45 NW 08 S** | S | PN 630 | 12 | M 20 x 1.5 | 27,5 | 19 | 24 | 9.0 x 1.5 |
| **DMO 45 NW 13 S** | S | PN 400 | 16 | M 24 x 1.5 | 31,5 | 27 | 30 | 12.0 x 2.0 |
| **DMO 45 NW 16 S** | S | PN 400 | 20 | M 30 x 2 | 36,0 | 30 | 36 | 16.3 x 2.4 |
| **DMO 45 NW 20 S** | S | PN 400 | 25 | M 36 x 2 | 40,5 | 36 | 46 | 20.3 x 2.4 |
| **DMO 45 NW 25 S** | S | PN 400 | 30 | M 42 x 2 | 44,5 | 50 | 50 | 25.3 x 2.4 |
| **DMO 45 NW 32 S** | S | PN 315 | 38 | M 52 x 2 | 50,5 | 50 | 60 | 33.3 x 2.4 |

Series: LL = Very light  L = Light  S = Heavy – PN = Nominal pressure  PB = Max. operating pressure – Ø d = External pipe diameter

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*