
VEWO 45
Fitting, angle 45°

HANSA-FLEX

Properties

Connection 1	metric nut thread
Sealing form 1	24° outer cone with O-ring
Connection 2	metric cylindrical outer thread
Sealing form 2	24° inner cone
Design	Adjustable direction fitting
Construction	Angle 45°
Scope of supply	Socket with union nut and cutting ring
Material	Steel
Surface	electro galvanised





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G1 + G2	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1	OR
VEWO 45 NW 04 HL	L	PN 315	6	M 12 x 1.5	26,0	9,0	24	14	14	4.0 x 1.5
VEWO 45 NW 06 HL	L	PN 315	8	M 14 x 1.5	27,5	12,0	27	14	17	6.0 x 1.5
VEWO 45 NW 08 HL	L	PN 315	10	M 16 x 1.5	29,0	12,0	27	19	19	7.5 x 1.5
VEWO 45 NW 10 HL	L	PN 315	12	M 18 x 1.5	29,5	14,0	29	19	22	9.0 x 1.5
VEWO 45 NW 13 HL	L	PN 315	15	M 22 x 1.5	32,5	17,0	32	22	27	12.0 x 2.0
VEWO 45 NW 16 HL	L	PN 315	18	M 26 x 1.5	35,5	16,5	33	27	32	15.0 x 2.0
VEWO 45 NW 20 HL	L	PN 160	22	M 30 x 2	38,5	18,5	35	30	36	20.0 x 2.0
VEWO 45 NW 25 HL	L	PN 160	28	M 36 x 2	41,5	23,0	40	36	41	26.0 x 2.0
VEWO 45 NW 32 HL	L	PN 160	35	M 45 x 2	51,0	26,5	48	50	50	32.0 x 2.5
VEWO 45 NW 40 HL	L	PN 160	42	M 52 x 2	56,0	26,0	49	50	60	38.0 x 2.5
VEWO 45 NW 03 HS	S	PN 630	6	M 14 x 1.5	27,0	9,0	24	14	17	4.0 x 1.5
VEWO 45 NW 04 HS	S	PN 630	8	M 16 x 1.5	27,5	12,0	27	19	19	6.0 x 1.5
VEWO 45 NW 06 HS	S	PN 630	10	M 18 x 1.5	30,0	13,5	30	19	22	7.5 x 1.5
VEWO 45 NW 08 HS	S	PN 630	12	M 20 x 1.5	31,0	16,5	33	19	24	9.0 x 1.5
VEWO 45 NW 13 HS	S	PN 400	16	M 24 x 1.5	36,5	15,5	34	19	30	12.0 x 2.0
VEWO 45 NW 16 HS	S	PN 400	20	M 30 x 2	44,5	16,0	38	27	36	16.3 x 2.4
VEWO 45 NW 20 HS	S	PN 400	25	M 36 x 2	50,0	18,5	43	36	46	20.3 x 2.4
VEWO 45 NW 25 HS	S	PN 400	30	M 42 x 2	55,0	23,5	50	50	50	25.3 x 2.4
VEWO 45 NW 32 HS	S	PN 315	38	M 52 x 2	63,0	21,0	52	50	60	33.3 x 2.4

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

VEWO 45 VA	Fitting, angle 45°, Stainless steel
XVEWO 45	Fitting, angle 45°, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.