


### Properties

<b>Connection 1</b>	metric nut thread
<b>Sealing form 1</b>	24° outer cone with O-ring
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	24° inner cone
<b>Design</b>	Adjustable direction fitting
<b>Construction</b>	Angle 90°
<b>Standard</b>	ISO 8434-1
<b>Scope of supply</b>	Socket (without union nut and cutting ring)
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

### Item

Identification	Series	Operating pressure	Ø d2 (mm)	M	L2 (mm)	L3 (mm)	L7 (mm)	AF (mm)	S1	OR
XVEWO NW 04 HL	L	PN 315	6	M 12 x 1.5	12,0	25,0	19	12	14	4.0 x 1.5
XVEWO NW 06 HL	L	PN 315	8	M 14 x 1.5	14,0	26,5	21	12	17	6.0 x 1.5
XVEWO NW 08 HL	L	PN 315	10	M 16 x 1.5	15,0	29,0	22	14	19	7.5 x 1.5
XVEWO NW 10 HL	L	PN 315	12	M 18 x 1.5	17,0	29,5	24	17	22	9.0 x 1.5
XVEWO NW 13 HL	L	PN 315	15	M 22 x 1.5	21,0	33,0	28	19	27	12.0 x 2.0
XVEWO NW 16 HL	L	PN 315	18	M 26 x 1.5	23,5	35,5	31	24	32	15.0 x 2.0
XVEWO NW 20 HL	L	PN 160	22	M 30 x 2	27,5	39,5	35	27	36	20.0 x 2.0
XVEWO NW 25 HL	L	PN 160	28	M 36 x 2	30,5	43,0	38	36	41	26.0 x 2.0
XVEWO NW 32 HL	L	PN 160	35	M 45 x 2	34,5	51,5	45	41	50	32.0 x 2.5
XVEWO NW 40 HL	L	PN 160	42	M 52 x 2	40,0	56,0	51	50	60	38.0 x 2.5
XVEWO NW 03 HS	S	PN 630	6	M 14 x 1.5	16,0	27,0	23	12	17	4.0 x 1.5
XVEWO NW 04 HS	S	PN 630	8	M 16 x 1.5	17,0	27,5	24	14	19	6.0 x 1.5
XVEWO NW 06 HS	S	PN 630	10	M 18 x 1.5	17,5	30,5	25	17	22	7.5 x 1.5
XVEWO NW 08 HS	S	PN 630	12	M 20 x 1.5	21,5	31,5	29	17	24	9.0 x 1.5
XVEWO NW 10 HS	S	PN 630	14	M 22 x 1.5	22,0	36,5	30	19	27	10.0 x 2.0
XVEWO NW 13 HS	S	PN 400	16	M 24 x 1.5	24,5	37,5	33	24	30	12.0 x 2.0
XVEWO NW 16 HS	S	PN 400	20	M 30 x 2	26,5	45,0	37	27	36	
XVEWO NW 20 HS	S	PN 400	25	M 36 x 2	30,0	50,5	42	36	46	
XVEWO NW 25 HS	S	PN 400	30	M 42 x 2	35,5	55,0	49	41	50	25.3 x 2.4
XVEWO NW 32 HS	S	PN 315	38	M 52 x 2	41,0	62,4	57	50	60	33.3 x 2.4

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

### Product versions

<b>XVEWO VA</b>	Fitting, angle 90°, Stainless steel
<b>VEWO</b>	Fitting, angle 90°, Steel